

Package ‘gamlss.demo’

October 13, 2022

Description Demos for smoothing and gamlss.family distributions.

Title Demos for GAMLSS

LazyLoad yes

Version 4.3-3

Date 2015-07-16

Depends R (>= 2.4.0), rpanel (>= 1.1-1), gamlss.dist, gamlss.tr,
tcltk, graphics, stats, grDevices

Suggests MASS

Author Mikis Stasinopoulos <d.stasinopoulos@londonmet.ac.uk>, Bob Rigby <r.rigby@londonmet.ac.uk>, Paul Eilers <p.eilers@erasmusmc.nl>, Brian Marx \email{bmarx@LSU.EDU}, Konstantinos Pateras <kostas.pateras@gmail.com> with contributions from Larisa Kosidou.

Maintainer Mikis Stasinopoulos <d.stasinopoulos@londonmet.ac.uk>

License GPL-2 | GPL-3

URL <http://www.gamlss.org/>

NeedsCompilation no

Repository CRAN

Date/Publication 2015-07-17 00:23:27

R topics documented:

demo.BSplines	2
demo.LocalRegression	3
demo.Locmean	4
demo.NO	5
demoDist	8
demoLpolyS	9
demoPsplines	10
gamlss.demo	11
Locmean	12

Index

15

`demo.BSplines`*Demos for smoothing techniques*

Description

These are demos for teaching smoothing techniques to students

Usage

```
demo.BSplines()
demo.RandomWalk(y = NULL, ...)
demo.histSmo(y = NULL, ...)
demo.interpolateSmo(y = NULL, w = NULL, ...)
demo.PSplines(y = NULL, x = NULL, ...)
```

Arguments

<code>y</code>	for <code>y</code> variable if needed otherwise it is generated
<code>w</code>	for weights if needed
<code>x</code>	for explanatory variable if needed
<code>...</code>	for adding parameters in the plot

Value

An rpanel plot

Author(s)

Paul Eilers <p.eilers@erasmusmc.nl>, Brian Marx <bmarx@LSU.EDU>, and Mikis Stasinopoulos <d.stasinopoulos@londonmet.ac.uk>

References

- Bowman, Bowman, Gibson and Crawford (2008) rpanel, CRAN
- Eilers, P. H. C. and Marx, B. D. (1996). Flexible smoothing with B-splines and penalties (with comments and rejoinder). *Statist. Sci.*, **11**, 89-121.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape, (with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

Examples

```
demo.PSplines()
```

demo.LocalRegression Local Regression Smoothing

Description

This function demonstrate some characteristics of local regression Smoothing

Usage

```
demo.LocalRegression(y = NULL, x = NULL, span = 0.5,
                     position = trunc((n - 1)/2),
                     deg = 1)
LPOL(y, x, span = 0.5, position = trunc((n - 1)/2),
      w = rep(1, length(y)), deg = 1)
WLPO(y, x, sd = 0.5, position = trunc((n - 1)/2),
      w = rep(1, length(y)), deg = 1)
```

Arguments

y	The response variable
x	the explanatory variable
span	The smoothing parameters
sd	The standard deviation of a normal kernel used as smoothing parameter
position	The position of the target values in the x axis
w	weights
deg	The degree of the local polynomial

Details

The function `demo.LocalRegression` demonstrates some aspects of the Local (unweighed) polynomial regression. The functions `LPOL()` and `WLPO()` produce plots related to unweighed and weighted local polynomial regression respectively.

Value

All function produce plots.

Author(s)

Mikis Stasinopoulos

References

- R Development Core Team (2010) tcltk package, CRAN.
- Bowman, Bowman, Gibson and Crawford (2008) rpanel, CRAN
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

See also [demoDist](#), [gamlss.demo](#)

Examples

```
demo.LocalRegression()
n <- 100
x <- seq(0, 1, length = n)*1.4
y <- 1.2 + .3*sin(5 * x) + rnorm(n) * 0.2
op <- par(mfrow=c(2,2))
LPOL(y,x, deg=0, position=5)
title("(a) moving average")
LPOL(y,x, deg=1, position=75)
title("(b) linear poly")
WLPOL(y,x, deg=2, position=30)
title("(c) quadratic poly")
WLPOL(y,x, deg=3, position= 50)
title("(b) cubic poly")
par(op)
```

`demo.Locmean`

Demos for local polynomial smoothing

Description

Those are four demos to show weighed and unweighed local mean and polynomial smoothing.

Usage

```
demo.Locmean(y = NULL, x = NULL, ...)
demo.Locpoly(y = NULL, x = NULL, ...)
demo.WLocpoly(y = NULL, x = NULL, ...)
demo.WLocmean(y = NULL, x = NULL, ...)
```

Arguments

- y the response variable. If null it generates its own data
- x explanatory variable
- ... for extra argument in the plot

Value

It produces an rpanel plot

Author(s)

Mikis Stasinopoulos <d.stasinopoulos@londonmet.ac.uk>

References

- Bowman, Bowman, Gibson and Crawford (2008) rpanel, CRAN
- Eilers, P. H. C. and Marx, B. D. (1996). Flexible smoothing with B-splines and penalties (with comments and rejoinder). *Statist. Sci.*, **11**, 89-121.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape, (with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[demo.PSplines](#)

Examples

[demo.Locmean\(\)](#)

[demo.NO](#)

Demos for different gamlss.family distributions

Description

The demo functions for showing the `gamlss.family` distributions. The functions use the package `Rpanel`.

Usage

```
demo.NO()
demo.LO()
demo.NO.LO()
demo.GU()
demo.RG()
demo.exGAUS()
demo.PE()
demo.PE.NO()
demo.TF()
demo.TF.NO()
demo.EGB2()
demo.GT()
demo.JSU()
demo.JSUo()
demo.NET()
demo.SHASH()
demo.SEP1()
demo.SEP2()
demo.SEP3()
demo.SEP4()
demo.ST1()
demo.ST2()
demo.ST3()
demo.ST4()
demo.ST5()
demo.EXP()
demo.GA()
demo.LOGNO()
demo.NO.LOGNO()
demo.IG()
demo.WEI()
demo.WEI2()
demo.WEI3()
demo.BCCG()
demo.GG()
demo.GIG()
demo.ZAGA()
demo.ZAIG()
demo.BCT()
demo.BCPE()
demo.GB2()
demo.EGB2()
demo.BE()
demo.BEo()
demo.GB1()
demo.GT()
demo.BB()
```

```
demo.BEINF()
demo.BEINF0()
demo.BEINF1()
demo.BI()
demo.DEL()
demo.LG()
demo.NBI()
demo.NBII()
demo.PO()
demo.SICHEL()
demo.ZABI()
demo.ZAGA()
demo.ZALG()
demo.ZAP()
demo.ZIBI()
demo.ZIP()
demo.ZIP2()
demo.BCCG()
demo.GG()
demo.PIG()
demo.ZABB()
demo.ZIBB()
demo.ZANBI()
demo.ZINBI()
demo.ZIPIG()
demo.N0tr()
demo.GAttr()
demo.YULE()
demo.WARING()
demo.GEOM()
demo.IGAMMA()
demo.PARETO2()
demo.PARETO2o()
demo.SHASHo()
demo.SHASHo2()
demo.LOGITNO()
demo.LOGNO2()
demo.SN1()
demo.SN2()
demo.SST()
demo.TF2()
demo.DPO()
```

Value

An rpanel plot

Author(s)

Mikis Stasinopoulos <d.stasinopoulos@londonmet.ac.uk>, Bob Rigby <r.rigby@londonmet.ac.uk> with contribution from Larisa Kosidou.

References

- Bowman, Bowman, Gibson and Crawford (2008) rpanel, CRAN
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

Examples

```
demo.NO()
```

demoDist

Interface for demonstrating the gamlss.family distributions

Description

The function `demoDist` is an `tcltk` interface for plotting all the available `gamlss.family` distributions.

Usage

```
demoDist()
```

Value

It creates a `tcltk` menu

Author(s)

Konstantinos Pateras <kostas.pateras@gmail.com>

References

- R Development Core Team (2010) tcltk package, CRAN.
- Bowman, Bowman, Gibson and Crawford (2008) rpanel, CRAN
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

Examples

```
## do not run
demoDist()
```

demoLpolyS

Demo for local polynomial fits

Description

It starts the gamlss local plynomial demos demos. It is an tcltk interface for using the local polynolial demos.

Usage

```
demoLpolyS()
```

Value

It creates a tcltk menu

Author(s)

Konstantinos Pateras <kostas.pateras@gmail.com>

References

- R Development Core Team (2010) tcltk package, CRAN.
- Bowman, Bowman, Gibson and Crawford (2008) rpanel, CRAN
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

See also [demoDist](#), [gamlss.demo](#),

Examples

`demoLpolyS()`

`demoPsplines`

Interface for demonstrating the P-splines and other smoothers

Description

The function `demoPsplines` is an `tcltk` interface for P. Eilers and B. Marx demos for P-splines.

Usage

`demoPsplines()`

Value

Create an `tcltk` menu

Author(s)

Konstantinos Pateras <kostas.pateras@gmail.com>

References

- R Development Core Team (2010) `tcltk` package, CRAN.
- Bowman, Bowman, Gibson and Crawford (2008) `rpanel`, CRAN
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

See also [demoDist](#), [~~~](#)

Examples

```
demoPsplines()
```

gamlss.demo

The demo for gamlss distributions and smoothing

Description

It starts the gamlss demos. It is an tcltk interface for using the gamlss demos.

Usage

```
gamlss.demo()
```

Value

It creates a tcltk menu

Author(s)

Konstantinos Pateras <kostas.pateras@gmail.com>

References

R Development Core Team (2010) tcltk package, CRAN.

Bowman, Bowman, Gibson and Crawford (2008) rpanel, CRAN

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

See also [demoDist](#), [gamlss.demo](#),

Examples

```
gamlss.demo()
```

Description

There are four function here to illustrate the fitting of local regressions. i) Locmean, which uses local means within a symmetric local window, ii) Locpoly, which uses a local polynomial fit within a symmetric local window. iii) WLocmean, which uses a Gaussian kernel and iv) WLocpoly, which uses local polynomials weighted by a Gaussian kernel

Usage

```
Locmean(y, x = seq(1, length(y)), w = rep(1, length(y)), span = 0.5)
Locpoly(y, x = seq(1, length(y)), w = rep(1, length(y)), span = 0.5, order = 1)
WLocmean(y, x = seq(1, length(y)), w = rep(1, length(y)), lambda = 0.5)
WLocpoly(y, x = seq(1, length(y)), w = rep(1, length(y)), lambda = 0.5, order = 1)
```

Arguments

y	the response variable
x	the x-variable
w	prior weights
span	the side of the local window compare as a proportion to the total number of observations
lambda	the smoothing parameter for the Gaussian kernel
order	the order of the polynomial

Details

Those functions can be used for illustration of the basic concepts of smoothing using small data sets. Do not use them with large data because are computationally inefficient.

Value

The functions return a locW object with values

fitted.values	the fitted values
residuals	the residuals
edf	the effective degrees of freedom
rss	the residual sum of squares
lambda	the smoothing parameter
y	the y variable
x	the x variable
w	the prior weights

Author(s)

Mikis Stasinopoulos, <d.stasinopoulos@londonmet.ac.uk>

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>)
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[loess](#), [ksmooth](#)

Examples

```
library(MASS)
data(mcycle)
# local means
m0<-Locmean(mcycle$accel, mcycle$times, span=.1)
m1<-Locmean(mcycle$accel, mcycle$times, span=.2)
m2<-Locmean(mcycle$accel, mcycle$times, span=.3)
span <- c("span=0.1", "span=0.2", "span=0.3")
plot.accel~times, data=mcycle,main="local mean")
lines(fitted(m0)~mcycle$times, col=1, lty=1)
lines(fitted(m1)~mcycle$times, col=2, lty=2)
lines(fitted(m2)~mcycle$times, col=3, lty=3)
legend(1.5,50, legend = span, col = 1:3,
       lty = 1:3, cex = .8, y.intersp = 1)
# kernel estimation
k0<-WLocmean(mcycle$accel, mcycle$times, lambda=1)
k1<-WLocmean(mcycle$accel, mcycle$times, lambda=2)
k2<-WLocmean(mcycle$accel, mcycle$times, lambda=3)
lambda <- c("lambda=1", "lambda=2", "lambda=3")
plot.accel~times, data=mcycle,main="Gaussian kernel fit")
lines(fitted(k0)~mcycle$times, col=1, lty=1)
lines(fitted(k1)~mcycle$times, col=2, lty=2)
lines(fitted(k2)~mcycle$times, col=3, lty=3)
legend(1.5,50, legend = lambda, col = 1:3,
       lty = 1:3, cex = .8, y.intersp = 1)
# local polynomials
l1<-Locpoly(mcycle$accel, mcycle$times, span=.1)
l2<-Locpoly(mcycle$accel, mcycle$times, span=.2)
l3<-Locpoly(mcycle$accel, mcycle$times, span=.3)

span <- c("span=0.1", "span=0.2", "span=0.3")
```

```
plot(accel~times, data=mcycle, main="local linear fit")
lines(fitted(l1)~mcycle$times, col=1, lty=1)
lines(fitted(l2)~mcycle$times, col=2, lty=2)
lines(fitted(l3)~mcycle$times, col=3, lty=3)
legend(1.5,50, legend = span, col = 1:3,
       lty = 1:3, cex = .8, y.intersp = 1)
# weighted local polynomials
lw1<-WLocpoly(mcycle$accel, mcycle$times, lambda=1.5, order=1)
lw2<-WLocpoly(mcycle$accel, mcycle$times, lambda=1.5, order=2)
lw3<-WLocpoly(mcycle$accel, mcycle$times, lambda=1.5, order=3)

span <- c("linear", "quadratic", "cubic")
plot(accel~times, data=mcycle, main="Weighted local linear, quadratic and cubic fits")
lines(fitted(lw1)~mcycle$times, col=1, lty=1)
lines(fitted(lw2)~mcycle$times, col=2, lty=2)
lines(fitted(lw3)~mcycle$times, col=3, lty=3)
legend(1.5,50, legend = span, col = 1:3,
       lty = 1:3, cex = .8, y.intersp = 1)
```

Index

- * **distribution**
 - demo.NO, 5
 - demoDist, 8
- * **regression**
 - demo.BSplines, 2
 - demo.LocalRegression, 3
 - demo.Locmean, 4
 - demo.NO, 5
 - demoDist, 8
 - demoLpolyS, 9
 - demoPsplines, 10
 - gamlss.demo, 11
 - Locmean, 12
 - demo.BB (demo.NO), 5
 - demo.BCCG (demo.NO), 5
 - demo.BCPE (demo.NO), 5
 - demo.BCT (demo.NO), 5
 - demo.BE (demo.NO), 5
 - demo.BEINF (demo.NO), 5
 - demo.BEINF0 (demo.NO), 5
 - demo.BEINF1 (demo.NO), 5
 - demo.BEo (demo.NO), 5
 - demo.BI (demo.NO), 5
 - demo.BSplines, 2
 - demo.DEL (demo.NO), 5
 - demo.DPO (demo.NO), 5
 - demo.EGB2 (demo.NO), 5
 - demo.exGAUS (demo.NO), 5
 - demo.EXP (demo.NO), 5
 - demo.GA (demo.NO), 5
 - demo.GAtr (demo.NO), 5
 - demo.GB1 (demo.NO), 5
 - demo.GB2 (demo.NO), 5
 - demo.GEOM (demo.NO), 5
 - demo.GG (demo.NO), 5
 - demo.GIG (demo.NO), 5
 - demo.GT (demo.NO), 5
 - demo.GU (demo.NO), 5
 - demo.histSmo (demo.BSplines), 2
 - demo.IG (demo.NO), 5
 - demo.IGAMMA (demo.NO), 5
 - demo.interpolateSmo (demo.BSplines), 2
 - demo.JSU (demo.NO), 5
 - demo.JSUo (demo.NO), 5
 - demo.LG (demo.NO), 5
 - demo.LO (demo.NO), 5
 - demo.LocalRegression, 3
 - demo.Locmean, 4
 - demo.Locpoly (demo.Locmean), 4
 - demo.LOGITNO (demo.NO), 5
 - demo.LOGNO (demo.NO), 5
 - demo.LOGNO2 (demo.NO), 5
 - demo.NBI (demo.NO), 5
 - demo.NBII (demo.NO), 5
 - demo.NET (demo.NO), 5
 - demo.NO, 5
 - demo.Notr (demo.NO), 5
 - demo.PARETO2 (demo.NO), 5
 - demo.PARETO2o (demo.NO), 5
 - demo.PE (demo.NO), 5
 - demo.PIG (demo.NO), 5
 - demo.PO (demo.NO), 5
 - demo.PSplines, 5
 - demo.PSplines (demo.BSplines), 2
 - demo.RandomWalk (demo.BSplines), 2
 - demo.RG (demo.NO), 5
 - demo.SEP1 (demo.NO), 5
 - demo.SEP2 (demo.NO), 5
 - demo.SEP3 (demo.NO), 5
 - demo.SEP4 (demo.NO), 5
 - demo.SHASH (demo.NO), 5
 - demo.SHASHo (demo.NO), 5
 - demo.SHASHo2 (demo.NO), 5
 - demo.SICHEL (demo.NO), 5
 - demo.SN1 (demo.NO), 5
 - demo.SN2 (demo.NO), 5
 - demo.SST (demo.NO), 5
 - demo.ST1 (demo.NO), 5

demo.ST2 (demo.NO), 5
demo.ST3 (demo.NO), 5
demo.ST4 (demo.NO), 5
demo.ST5 (demo.NO), 5
demo.TF (demo.NO), 5
demo.TF2 (demo.NO), 5
demo.WARING (demo.NO), 5
demo.WEI (demo.NO), 5
demo.WEI2 (demo.NO), 5
demo.WEI3 (demo.NO), 5
demo.WLocmean (demo.Locmean), 4
demo.WLocpoly (demo.Locmean), 4
demo.YULE (demo.NO), 5
demo.ZABB (demo.NO), 5
demo.ZABI (demo.NO), 5
demo.ZAGA (demo.NO), 5
demo.ZAIG (demo.NO), 5
demo.ZALG (demo.NO), 5
demo.ZANBI (demo.NO), 5
demo.ZAP (demo.NO), 5
demo.ZIBB (demo.NO), 5
demo.ZIBI (demo.NO), 5
demo.ZINBI (demo.NO), 5
demo.ZIP (demo.NO), 5
demo.ZIP2 (demo.NO), 5
demo.ZIPIG (demo.NO), 5
demoDist, 4, 8, 10, 11
demoPolyS, 9
demoPsplines, 10

gamlss.demo, 4, 10, 11, 11

ksmooth, 13

Locmean, 12
Locpoly (Locmean), 12
loess, 13
LPOL (demo.LocalRegression), 3

WLocmean (Locmean), 12
WLocpoly (Locmean), 12
WLPOL (demo.LocalRegression), 3