

Package ‘wfg’

October 12, 2022

Type Package

Title Weighted Fast Greedy Algorithm

Version 0.1

Date 2016-02-21

Author Han Yu [aut, cre], Rachael Hageman Blair [aut]

Maintainer Han Yu <hyu9@buffalo.edu>

Depends R (>= 3.1.0), igraph

Description Implementation of Weighted Fast Greedy algorithm for community detection in networks with mixed types of attributes.

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2016-02-25 00:23:11

R topics documented:

network.simu	1
wfg	3

Index	5
--------------	----------

network.simu	<i>Simulation of Networks with Community Structures</i>
--------------	---

Description

Simulation of networks under the framework by Girvan and Newman. The vertices are connected with each other randomly and independents with probability $p.in$ (within same community) and $p.out$ (between communities).

Usage

```
network.simu(nv = c(32, 32, 32, 32),  
             p.in = c(0.323, 0.323, 0.323, 0.323),  
             p.out = 0.0625, p.del = 0)
```

Arguments

<code>nv</code>	a vector of community sizes. The number of communities equals the number of elements in this vector.
<code>p.in</code>	a vector of probability of a node to be randomly linked to other nodes in the same community.
<code>p.out</code>	the probability of a node to be randomly linked to nodes in other communities.
<code>p.del</code>	the proportion of links that are randomly deleted.

Value

<code>net</code>	The simulated network.
<code>group</code>	The membership of vertices.

Author(s)

Han Yu & Rachael Hageman Blair

References

Girvan, Michelle, and Mark EJ Newman. "Community structure in social and biological networks." Proceedings of the national academy of sciences 99.12 (2002): 7821-7826.

Examples

```
## simulation of a network with four communities, each with size 32  
  
library(wfg)  
nv = c(32, 32, 32, 32)  
p.in = c(0.452, 0.452, 0.452, 0.452)  
p.out = 0.021  
p.del = 0  
net.simu <- network.simu(nv=nv, p.in=p.in, p.out=p.out, p.del=p.del)  
net <- net.simu$net  
group <- net.simu$group  
  
## plot simulated network with vertices colored by membership  
  
V(net)$size <- 7  
V(net)$color <- group  
plot(net, vertex.label='')
```

wfg	<i>Weighted Fast Greedy Algorithm</i>
-----	---------------------------------------

Description

Implementation of weighted fast greedy algorithm for community detection in networks with mixed types of attributes.

Usage

```
wfg(net, attr=NULL, under.sample=FALSE, prioritize=FALSE)
```

Arguments

net	network for community detection
attr	data frame of attribute information. The default value is NULL, when no attribute information will be used. Under default this method is identical to fast greedy community detection algorithm.
under.sample	a boolean parameter. When it is TRUE, the vertex pairs without links will be under-sampled to have the same number as that of the linked pairs of vertices.
prioritize	a boolean parameter. When it is TRUE, a matrix of community-specific coefficients will be returned, by which the communities can be prioritized.

Details

Each column of attr data frame can be a vector with type of either numeric (continuous) or factor (categorical). The matrix of community-specific coefficients gives estimates as to the relative homogeneity of each attribute within each community. Specifically, a negative beta with large absolute value indicates corresponding attribute is homogeneous.

Value

beta	Estimates of coefficients from logistic regression.
beta.matrix	Estimates of community specific coefficients.
memb	Community membership of vertices.

Author(s)

Han Yu & Rachael Hageman Blair

References

Clauset, Aaron, Mark EJ Newman, and Cristopher Moore. "Finding community structure in very large networks." Physical review E 70.6 (2004): 066111.

Examples

```
##### implementation of wfg on a computer generated network with
##### structurally relevant continuous attribute and irrelevant categorical attribute
set.seed(7)
##### set network properties
## four groups, each with 32 vertices
nv <- c(32,32,32,32)
l <- length(nv)
## obtain p.in and p.out from z.out
z.out <- 6
z.in <- 16-z.out
p.out <- z.out/96
p.in <- rep(z.in/31, l)

##### simulate network
net.simu <- network.simu(nv=nv, p.in=p.in, p.out=p.out, p.del=0)
net <- net.simu$net
group <- net.simu$group

##### simulate attributes
## separation of continuous attribute
delta <- 1
## p's for the multinomial distribution of categorical attributes
p1 <- 0.25
p2 <- (1-p1)/3
attr1 <- c(rnorm(nv[1],0), rnorm(nv[2],1*delta), rnorm(nv[3],2*delta), rnorm(nv[4],3*delta))
attr2 <- c(sample(c(1,2,3,4), size=nv[1], prob=c(p1, p2, p2, p2), replace=TRUE),
           sample(c(1,2,3,4), size=nv[2], prob=c(p2, p1, p2, p2), replace=TRUE),
           sample(c(1,2,3,4), size=nv[3], prob=c(p2, p2, p1, p2), replace=TRUE),
           sample(c(1,2,3,4), size=nv[4], prob=c(p2, p2, p2, p1), replace=TRUE))
attributes <- data.frame(attr1, attr2)

##### implementation of wfg
wfg.result <- wfg(net=net, attr=attributes, under.sample = FALSE, prioritize = TRUE)

##### plot network colored by wfg result
V(net)$size <- 7
V(net)$color <- wfg.result$memb
plot(net, vertex.label='')
```

Index

`network.simu`, 1

`wfg`, 3