

Package ‘marquee’

May 28, 2024

Title Markdown Parser and Renderer for R Graphics

Version 0.1.0

Description Provides the mean to parse and render markdown text with grid along with facilities to define the styling of the text.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.1

LinkingTo cpp11

Imports cli, glue, grid, jpeg, png, rlang (>= 1.1.0), systemfonts (>= 1.1.0), textshaping (>= 0.4.0), utils, vctrs

Suggests ggplot2, gt, knitr, patchwork, ragg, rmarkdown, rsvg, testthat (>= 3.0.0)

URL <https://marquee.r-lib.org>, <https://github.com/r-lib/marquee>

BugReports <https://github.com/r-lib/marquee/issues>

Config/Needs/website tidyverse/tidytemplate

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation yes

Author Thomas Lin Pedersen [aut, cre]
(<<https://orcid.org/0000-0002-5147-4711>>),
Martin Mitáš [aut] (Author of MD4C),
Posit Software, PBC [cph, fnd]

Maintainer Thomas Lin Pedersen <thomas.pedersen@posit.co>

Repository CRAN

Date/Publication 2024-05-28 16:20:02 UTC

R topics documented:

| | |
|---------------------------|----|
| classic_style | 2 |
| element_marquee | 4 |
| geom_marquee | 5 |
| marquee_glue | 8 |
| marquee_grob | 11 |
| marquee_parse | 13 |
| style | 16 |
| style-helpers | 19 |
| style_set | 20 |

| | |
|--------------|-----------|
| Index | 22 |
|--------------|-----------|

| | |
|---------------|-------------------------------------|
| classic_style | <i>Classic styling for markdown</i> |
|---------------|-------------------------------------|

Description

This function facilitates construction of a complete style set based on the classic look of an HTML rendered markdown document. It contains style specifications for all the supported markdown elements as well as a sub and sup style that can be used for subscripts and superscript respectively. These are only accessible through custom spans (e.g. $H\{.sub 2\}0$) as markdown doesn't provide a syntax for these formats.

Usage

```
classic_style(
  base_size = 12,
  body_font = "",
  header_font = "",
  code_font = "mono",
  ...
)
```

Arguments

| | |
|-------------|---|
| base_size | The base font size for the text. All other sizing is based on this |
| body_font | The font family to use for body text |
| header_font | The font family to use for headers |
| code_font | The font family to use for code and code block text |
| ... | Arguments passed on to base_style |
| weight | The font weight to use. Can either be a number (0, 100, 200, 300, 400, 500, 600, 700, 800, or 900) or a strings ("undefined", "thin", "ultralight", "light", "normal", "medium", "semibold", "bold", "ultrabold", or "heavy") |

italic Should the font be slanted

width The font width to use. Can either be a number ('0', '1', '2', '3', '4', '5', '6', '7', '8', or '9') or strings ("undefined", "ultracondensed", "extracondensed", "condensed", "semicondensed", "normal", "semiexpanded", "expanded", "extraexpanded", or "ultraexpanded")

features A [font_feature](#) object specifying any OpenType font features to apply to the font

color Is the color of the font

lineheight The spacing between subsequent lines relative to the font size. Can be [relative\(\)](#) in which case it is based on the parent lineheight.

align The alignment within the text. One of "left", "center", "right", "justified-left", "justified-center", "justified-right", or "distributed"

tracking Additional character spacing measured in 1/1000em. Can be [relative\(\)](#) in which case it is based on the parent tracking.

indent The indentation of the first line in a paragraph measured in points. Can be [relative\(\)](#) in which case it is based on the parent indent, [em\(\)](#) in which case it is based on the font size in this style, or [rem\(\)](#) in which case it is based on the font size of the body element.

hanging The indentation of all but the first line in a paragraph measured in points. Can be [relative\(\)](#) in which case it is based on the parent hanging, [em\(\)](#) in which case it is based on the font size in this style, or [rem\(\)](#) in which case it is based on the font size of the body element.

margin The margin around the element, given as a call to [trbl\(\)](#)

padding The padding around the element, given as a call to [trbl\(\)](#)

background The color of the background fill. The background includes the padding but not the margin. Can be a solid color or a gradient or pattern made with [grid::linearGradient\(\)](#)/[grid::radialGradient\(\)](#)/[grid::pattern\(\)](#)

border The color of the background stroke. The background includes the padding but not the margin

border_size The line width of the background stroke, given as a call to [trbl\(\)](#)

border_radius The corner radius of the background, given in points

bullets A vector of strings to use for bullets in unordered lists. [marquee_bullets](#) provides a selection

underline Should text be underlined

strikethrough Should text be strikethrough

baseline The baseline shift to apply to the text

img_asp The default aspect ratio for block level images if not provided by the image itself

Value

A style set object

Examples

```
classic_style(16, "serif", "sans")
```

element_marquee *ggplot2 theme element supporting marquee syntax*

Description

This theme element is a drop-in replacement for `ggplot2::element_text()`. It works by integrating the various style settings of the element into the base style of the provided style set. If a margin is given, it is set on the body tag with `skip_inherit()`. The default width is NA meaning that it will span as long as the given text is, doing no line wrapping. You can set it to any unit to make it fit within a specific width. However, this may not work as expected with rotated text (you may get lucky). Note that you may see small shifts in the visuals when going from `element_text()` to `element_marquee()` as size reporting may differ between the two elements.

Usage

```
element_marquee(
  family = NULL,
  colour = NULL,
  size = NULL,
  hjust = NULL,
  vjust = NULL,
  angle = NULL,
  lineheight = NULL,
  color = NULL,
  margin = NULL,
  style = NULL,
  width = NULL,
  inherit.blank = FALSE
)
```

Arguments

| | |
|---------------|---|
| family | The font family of the base style |
| colour, color | The font colour of the base style |
| size | The font size of the base style |
| hjust | Horizontal justification (in [0, 1]) |
| vjust | Vertical justification (in [0, 1]) |
| angle | Angle (in [0, 360]) |
| lineheight | The lineheight of the base style |
| margin | The margin for the body tag |
| style | A style set to base the rendering on |
| width | The maximum width of the text. See the description for some caveats for this |
| inherit.blank | Should this element inherit the existence of an <code>element_blank</code> among its parents? If TRUE the existence of a blank element among its parents will cause this element to be blank as well. If FALSE any blank parent element will be ignored when calculating final element state. |

Value

An `element_marquee` object that can be used in place of `element_text` in `ggplot2` theme specifications

Examples

```
library(ggplot2)
p <- ggplot(mtcars) +
  geom_point(aes(mpg, disp)) +
  labs(title = "A {.red *marquee*} title\n* Look at this bullet list\n\n* great, huh?") +
  theme_gray(base_size = 6) +
  theme(title = element_marquee())

plot(p)

ggplot(mtcars) +
  geom_histogram(aes(x = mpg)) +
  labs(title =
    "I put a plot in your title so you can plot while you title



What more could you _possibly_ want?") +
  theme(title = element_marquee())
```

geom_marquee

Draw text formatted with marquee

Description

The geom is an extension of `geom_text()` and `geom_label()` that allows you to draw richly formatted text in marquee-markdown format in your plot. For plain text it is a near-drop-in replacement for the above geoms except some sizing might be very slightly different. However, using this geom you are able to access the much more powerful font settings available in marquee, so even then it might make sense to opt for this geom.

Usage

```
geom_marquee(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  ...,
  size.unit = "mm",
  na.rm = FALSE,
```

```

  show.legend = NA,
  inherit.aes = TRUE
)

```

Arguments

| | |
|----------|---|
| mapping | Set of aesthetic mappings created by aes() . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping. |
| data | <p>The data to be displayed in this layer. There are three options:</p> <p>If <code>NULL</code>, the default, the data is inherited from the plot data as specified in the call to ggplot().</p> <p>A <code>data.frame</code>, or other object, will override the plot data. All objects will be fortified to produce a data frame. See fortify() for which variables will be created.</p> <p>A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code>, and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>).</p> |
| stat | <p>The statistical transformation to use on the data for this layer. When using a <code>geom_*()</code> function to construct a layer, the <code>stat</code> argument can be used to override the default coupling between geoms and stats. The <code>stat</code> argument accepts the following:</p> <ul style="list-style-type: none"> • A Stat ggproto subclass, for example <code>StatCount</code>. • A string naming the stat. To give the stat as a string, strip the function name of the <code>stat_</code> prefix. For example, to use <code>stat_count()</code>, give the stat as "count". • For more information and other ways to specify the stat, see the layer stat documentation. |
| position | <p>A position adjustment to use on the data for this layer. Cannot be jointly specified with <code>nudge_x</code> or <code>nudge_y</code>. This can be used in various ways, including to prevent overplotting and improving the display. The <code>position</code> argument accepts the following:</p> <ul style="list-style-type: none"> • The result of calling a position function, such as <code>position_jitter()</code>. • A string naming the position adjustment. To give the position as a string, strip the function name of the <code>position_</code> prefix. For example, to use <code>position_jitter()</code>, give the position as "jitter". • For more information and other ways to specify the position, see the layer position documentation. |
| ... | <p>Other arguments passed on to layer()'s <code>params</code> argument. These arguments broadly fall into one of 4 categories below. Notably, further arguments to the <code>position</code> argument, or aesthetics that are required can <i>not</i> be passed through ... Unknown arguments that are not part of the 4 categories below are ignored.</p> <ul style="list-style-type: none"> • Static aesthetics that are not mapped to a scale, but are at a fixed value and apply to the layer as a whole. For example, <code>colour = "red"</code> or <code>linewidth = 3</code>. The geom's documentation has an Aesthetics section that lists the available options. The 'required' aesthetics cannot be passed on to the |

params. Please note that while passing unmapped aesthetics as vectors is technically possible, the order and required length is not guaranteed to be parallel to the input data.

- When constructing a layer using a `stat_*()` function, the `...` argument can be used to pass on parameters to the geom part of the layer. An example of this is `stat_density(geom = "area", outline.type = "both")`. The geom's documentation lists which parameters it can accept.
- Inversely, when constructing a layer using a `geom_*()` function, the `...` argument can be used to pass on parameters to the stat part of the layer. An example of this is `geom_area(stat = "density", adjust = 0.5)`. The stat's documentation lists which parameters it can accept.
- The `key_glyph` argument of `layer()` may also be passed on through `...`. This can be one of the functions described as [key glyphs](#), to change the display of the layer in the legend.

| | |
|--------------------------|---|
| <code>size.unit</code> | How the size aesthetic is interpreted: as millimetres ("mm", default), points ("pt"), centimetres ("cm"), inches ("in"), or picas ("pc"). |
| <code>na.rm</code> | If FALSE, the default, missing values are removed with a warning. If TRUE, missing values are silently removed. |
| <code>show.legend</code> | logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display. |
| <code>inherit.aes</code> | If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> . |

Details

Styling of the text is based on a style set with the exception that the standard aesthetics such as family, size, colour, fill, etc. are recognized and applied to the base tag style. The default style set ([classic_style](#)) can be changed using the style aesthetic which can take a vector of style sets so that each text can rely on it's own style if needed. As with `element_marquee()`, the fill aesthetic is treated differently and not applied to the base tag, but to the body tag as a `skip_inherit()` style so as to not propagate the fill.

Contrary to the standard text and label geoms, `geom_marquee()` takes a width aesthetic that can be used to turn on soft wrapping of text. The default value (NA) lets the text run as long as it want's (honoring hard breaks), but setting this to something else will instruct marquee to use at most that amount of space. You can use grid units to set it to an absolute amount.

Value

A ggplot2 layer that can be added to a plot

Examples

```
library(ggplot2)
```

```

# Standard use
p <- ggplot(mtcars, aes(wt, mpg))
p + geom_marquee(aes(label = rownames(mtcars)))

# Make use of more powerful font features (note, result may depend on fonts
# installed on the system)
p + geom_marquee(
  aes(label = rownames(mtcars)),
  style = classic_style(weight = "thin", width = "condensed")
)

# Turn on line wrapping
p + geom_marquee(aes(label = rownames(mtcars)), width = unit(2, "cm"))

# Style like label
label_style <- modify_style(
  classic_style(),
  "body",
  padding = skip_inherit(trbl(4)),
  border = "black",
  border_size = skip_inherit(trbl(1)),
  border_radius = 3
)
p + geom_marquee(aes(label = rownames(mtcars), fill = gear), style = label_style)

# Use markdown to style the text
red_bold_names <- sub("(\\w+)", "{.red **\\1**}", rownames(mtcars))
p + geom_marquee(aes(label = red_bold_names))

```

marquee_glue

Marquee-aware string interpolation

Description

If you want to create your markdown programmatically you'd probably want to use some sort of string interpolation such as `glue()`. However, the custom span syntax of `marquee` interferes with the standard interpolation syntax of `glue`. This function lets you use both together.

Usage

```

marquee_glue(
  ...,
  .sep = "",
  .envir = parent.frame(),
  .open = "{",
  .close = "}",
  .na = "NA",
  .null = character(),

```



```

    .comment = character(),
    .literal = FALSE,
    .transformer = NULL,
    .trim = TRUE
  )

marquee_glue_data(
  .x,
  ...,
  .sep = "",
  .envir = parent.frame(),
  .open = "{",
  .close = "}",
  .na = "NA",
  .null = character(),
  .comment = character(),
  .literal = FALSE,
  .transformer = NULL,
  .trim = TRUE
)

```

Arguments

| | |
|--------|--|
| ... | [expressions] Unnamed arguments are taken to be expression string(s) to format. Multiple inputs are concatenated together before formatting. Named arguments are taken to be temporary variables available for substitution. For <code>`glue_data()`</code> , elements in <code>`...`</code> override the values in <code>`x`</code> . |
| .sep | [character(1): ""] Separator used to separate elements. |
| .envir | [environment: parent.frame()] Environment to evaluate each expression in. Expressions are evaluated from left to right. If <code>.x</code> is an environment, the expressions are evaluated in that environment and <code>.envir</code> is ignored. If <code>NULL</code> is passed, it is equivalent to <code>emptyenv()</code> . |
| .open | [character(1): '{'] The opening delimiter. Doubling the full delimiter escapes it. |
| .close | [character(1): '}'] The closing delimiter. Doubling the full delimiter escapes it. |
| .na | [character(1): 'NA'] Value to replace NA values with. If <code>NULL</code> missing values are propagated, that is an NA result will cause NA output. Otherwise the value is replaced by the value of <code>.na</code> . |
| .null | [character(1): 'character'] Value to replace <code>NULL</code> values with. If <code>character()</code> whole output is <code>character()</code> . If <code>NULL</code> all <code>NULL</code> values are dropped (as in <code>paste0()</code>). Otherwise the value is replaced by the value of <code>.null</code> . |

| | |
|---------------------------|---|
| <code>.comment</code> | [character(1): '#'] Value to use as the comment character. |
| <code>.literal</code> | [boolean(1): 'FALSE'] Whether to treat single or double quotes, backticks, and comments as regular characters (vs. as syntactic elements), when parsing the expression string. Setting <code>.literal = TRUE</code> probably only makes sense in combination with a custom <code>.transformer</code> , as is the case with <code>glue_col()</code> . Regard this argument (especially, its name) as experimental. |
| <code>.transformer</code> | [function] A function taking two arguments, <code>text</code> and <code>envir</code> , where <code>text</code> is the unparsed string inside the glue block and <code>envir</code> is the execution environment. A <code>.transformer</code> lets you modify a glue block before, during, or after evaluation, allowing you to create your own custom <code>glue()</code> -like functions. See <code>vignette("transformers")</code> for examples. |
| <code>.trim</code> | [logical(1): 'TRUE'] Whether to trim the input template with <code>trim()</code> or not. |
| <code>.x</code> | [listish] An environment, list, or data frame used to lookup values. |

Details

If you choose a different set of delimiters than `"{"` and `"}"` for the interpolation the functions will call the equivalent glue functions directly. However, if you keep the defaults, the functions will use a custom transformer that will make sure to keep the marquee custom span notation. You can both interpolate the content of the span, as well as the span class (see examples)

Value

A character vector

Examples

```
# standard use
red_text <- "this text will be red"
marquee_glue("This will be black and {.red {red_text}}!")

# if the span is not valid it will be treated as standard glue interpolation
try(
  marquee_glue("This will be black and {.red}!")
)

# You can interpolate the tag name as well
col <- "green"
marquee_glue("This will be black and {.{col} this text will be {col}}!")

# Tag name interpolation must follow a `.` or a `#` as these identify the
# bracket pair as a custom span class
col <- ".yellow"
# This is not what you want probably
```

```

marquee_glue("This will be black and {{col}} this text will be {col}}!")

# Tag interpolation should also interpolate the full tag and be followed by
# a space in order to be valid
part <- "1"
marquee_glue("This will be black and {.ye{part}low this text will be {col}}!")
try(
  marquee_glue("This will be black and {.part}avender this text will be {col}}!")
)

```

marquee_grob

Construct a grob rendering one or more markdown texts

Description

This is the main function of `marquee`. It takes a vector of markdown strings, parses them with the provided style, and returns a grob capable of rendering the parsed text into rich text and (possibly) images. See `marquee_parse()` for more information about how markdown is parsed and see details below for further information on how rendering proceeds.

Usage

```

marquee_grob(
  text,
  style = classic_style(),
  ignore_html = TRUE,
  x = 0,
  y = 1,
  width = NULL,
  default.units = "npc",
  hjust = "left",
  vjust = "top",
  angle = 0,
  vp = NULL,
  name = NULL
)

```

Arguments

| | |
|--------------------------|--|
| <code>text</code> | Either a character vector or a <code>marquee_parsed</code> object as created by <code>marquee_parse()</code> |
| <code>style</code> | A style set such as <code>classic_style()</code> that defines how the text should be rendered |
| <code>ignore_html</code> | Should HTML code be removed from the output |
| <code>x, y</code> | The location of the markdown text in the graphics. If numeric it will be converted to units using <code>default.units</code> |

| | |
|----------------------------|---|
| width | The width of each markdown text. If numeric it will be converted to units using <code>default.units</code> . NULL is equivalent to the width of the parent container |
| <code>default.units</code> | A string giving the default units to apply to <code>x</code> , <code>y</code> , and <code>width</code> |
| <code>hjust</code> | The horizontal justification of the markdown with respect to <code>x</code> . Can either be a numeric or one of "left", "left-ink", "center", "center-ink", "right-ink", or "right" |
| <code>vjust</code> | The vertical justification of the markdown with respect to <code>y</code> . Can either be a numeric or one of "bottom", "bottom-ink", "last-line", "center", "center-ink", "first-line", "top-ink", "top" |
| angle | The angle of rotation (in degrees) around <code>x</code> and <code>y</code> |
| <code>vp</code> | An optional viewport to assign to the grob |
| name | The name for the grob. If NULL a unique name will be generated |

Value

A grob of class `marquee`

Rendering style

The rendering more or less adheres to the styling provided by `marquee_parse()`, but has some intricacies as detailed below:

Tight lists

If a list is tight, the bottom margin of each `li` tag will be set so the spacing matches the lineheight. Further, the top margin will be set to 0.

Block images

In markdown, image tags are span elements so they can be placed inline. However, if an image tag is the only thing that is contained inside a `p` tag `marquee` determines that it should be considered a block element. In that case, the parent `p` element inherits the styling from the image element so that the image can e.g. adhere to `align` properties, or provide their own padding.

Horizontal rulers

These elements are rendered as an empty block. The standard style sets a bottom border size and no size for the other sides.

Margin collapsing

Margin calculations follows the margin collapsing rules of HTML. Read more about these at [mdn](#)

Underline and strikethrough

Underlines are placed 0.1em below the baseline of the text. Strikethrough are placed 0.3em above the baseline. The width of the line is set to 0.075em. It inherits the color of the text. No further styling is possible.

Spans with background

Consecutive spans with the same background and border settings are merged into a single rectangle. The padding of the span defines the size of the background but will not modify the placement of glyph (i.e. having a left padding will not move the first glyph further away from it's left neighbor).

Bullet position

Bullets are placed, right-aligned, 0.25em to the left of the first line in the li element.

Border with border radius

If borders are not the same on all sides they are drawn one by one. In this case the border radius is ignored.

Image rendering

The image tag can be used to place images. There are support for both png and jpeg images. If the path instead names a grob, ggplot, or patchwork object then this is rendered instead. If the file cannot be read, if it doesn't exist, or if the path names an object that is not a grob, ggplot or patchwork, a placeholder is rendered in it's place (black square with red cross).

Image sizing

There is no standard in markdown for specifying the size of images. By default, block-level images fill the width of it's container and maintain it's aspect ratio. Inline images have a default width of 0.65em and a height matching the aspect ration.

However, if you wish to control sizing, you can instead provide the image as a grob with a viewport with fixed dimensions, in which case this will be used as long as the width doesn't exceed the width of the container (in which case it will get downsized). If a rastergrob is provided without absolute sizing, the aspect ratio will match the raster, otherwise the aspect ratio will be taken from the styling of the element (defaults to 1.65)

Table rendering

While marquee does not support the extended table syntax for markdown it does allow you to include tables in the output. It does so by supporting gt objects as valid paths in image tags in the same way as ggplots etc. This meeans that you can style your tables any way you wish and with the full power of gt, which is much more flexible than the markdown table syntax.

Textbox justification

The justification options exceeds the classic ones provided by grid. While numeric values are available as always, the number of possible text values are larger. Horizontal justification add "left-ink", "center-ink", and "right-ink" which uses the left-most and right-most positioned glyph (or halfway between them) as anchors. Vertical justification has the equivalent "bottom-ink", "center-ink", and "top-ink" anchors, but also "first-line" and "last-line" which sets the anchor at the baseline of the first or last line respectively.

marquee_parse

Parse a text as marquee

Description

marquee uses an extension of CommonMark with no support for HTML code (it is rendered verbatim). The focus is to allow easy formatting of text for graphics, rather than fully fledged typesetting. See *marquee syntax* for more about the format.

Usage

```
marquee_parse(text, style = classic_style(), ignore_html = TRUE)
```

Arguments

| | |
|--------------------------|--|
| <code>text</code> | A character string. The core quality of markdown is that any text is valid markdown so there is no restrictions on the content |
| <code>style</code> | A style set such as <code>classic_style()</code> that defines how the text should be rendered |
| <code>ignore_html</code> | Should HTML code be removed from the output |

Value

A data frame describing the various tokens of the text and the style to apply to them. The output is mainly meant for programmatic consumption such as in `marquee_grob()`

marquee tags

marquee tokenizes the input text into blocks and spans. It recognises the following tags:

Block tags

`body` is the parent tag of a markdown document. It never contains any text itself, only other blocks.

`ul` is an unordered list. It contains a number of `li` children

`ol` is an ordered list. It contains a number of `li` children

`li` is a list element. If the list is tight it contains text directly inside of it. If not, text are placed inside child `p` blocks

`hr` is a horizontal line, spanning the width of the parent block. For styling, the bottom border size is used when rendering

`h1-h6` are headings at different levels

`cb` is a code block. Text inside code blocks are rendered verbatim, i.e. it cannot contain any children

`p` is a standard paragraph block. Text separated by two line-ends are separated into separate paragraphs

`qb` is a quote block. It may contain children

Span tags

`em` is an emphasized text span. Often this means italicizing the text, but it is ultimately up to the renderer

`str` is strong text, often rendered with bold text

`a` is a link text. While marquee rendering doesn't allow for links, it can still be rendered in a particular way

`code` is text rendered as code. Often this uses a monospaced font. Text inside this span is rendered verbatim

`u` is text that should be underlined

`del` is text that should have strikethrough

custom spans is a marquee specific extension to the syntax that allows you to make up tags on the fly. See the section on marquee syntax for more.

marquee syntax

marquee uses md4c which is a fully CommonMark compliant markdown parser. CommonMark is an effort to create an internally coherent markdown specification, something that was missing from the original markdown description. If you are used to writing markdown, you are used to CommonMark. Below is a list of notable additions or details about the specific way marquee handles CommonMark

Underlines and strikethrough

While not part of the basic CommonMark spec, underline and strikethrough are supported by marquee using `_` and `~` (e.g. `_underline this_` and `~this was an error~`).

Images

Image tags (`![image title](path/to/image)`) are supported, but the title is ignored. The path is returned as the token text.

HTML

HTML tags are ignored, i.e. they are rendered verbatim. This is not that different from classic markdown rendering except that people often convert markdown to HTML where these tags suddenly have meaning. They do not carry any special significance when rendered with marquee

Custom tags

While markdown provides most of what is necessary for standard text markup, there are situations, especially in visualisation, where we need something more. Often users reach for inline HTML spans for that, but since HTML is fully ignored in marquee this is not an option. Further, adding in HTML decreases readability of the unformatted text a lot.

With marquee you can create a custom span using the `{ . tag <some text>}` syntax, e.g. `{ .sm small text}` to wrap "small text" in the `sm` tag. You can alternatively use `{#tag <some text>}` for the same effect. The only difference is that in the former syntax the `.` is stripped from the tag name, whereas in the latter the `#` remains part of the name. See the Styling section for the primal use of the latter syntax.

Styling

During parsing, each token is assigned a style based on the provided style set. The styling is cascading, but without the intricacies of CSS. A child element inherits the styling of it's parent for the options that are set to NULL in the style matching the child tag. Any style element that are `relative()` are computed based on the value of the parent style element. `em()` elements are resolved based on the size element of the child style, and `rem()` elements are resolved using the size element of the body style. If a style is not provided for the tag, it fully inherits the style of it's parent.

Automatic coloring Recognizing that the primary use for custom tags may be to change the color of some text, marquee provides a shortcut for this. If a style is not found for the tag in the provided style set, marquee will check if the tag matches a valid color (i.e. a string from `grDevices::colors()`, or a valid hex string, e.g. `#53f2a9`). If it is a valid color it will set this as the font color of the style. This means that parsing `"Color { .red this} red"` automatically sets the color of "this" to red, even if no style is provided for the red tag. Likewise, parsing `"Color {#00FF00 me} green"` will automatically set the color of "me" to `#00FF00` (fully saturated green).

Additional parsing information

Apart from splitting the text up into tokens, `marquee_parse()` also provides some additional information useful for rendering the output in the expected way. The `id` column refers the tokens back to the original input text, the `block` relates tokens together into blocks. Block elements increment the block count when they are entered, and decrement it when they are exited. The `type` column provides the type of the block. The `indentation` column provides the node level in the tree. A child block will increase the indentation for as long as it is active. `ol_index` provides the number associated with the ordered list element. `tight` indicates whether the list is tight (i.e. it was provided with no empty lines between list elements). The `ends` column indicate until which row in the output the tag is active (i.e. the tag is closed after the row indicated by the value in this column).

Examples

```
marquee_parse("# Header of the example\nSome body text", classic_style())
```

| | |
|-------|--|
| style | <i>Create a style specification for a single tag</i> |
|-------|--|

Description

`style()` constructs a `marquee_style` object specifying the styling for a single tag. The meaning of `NULL` is to inherit the value from the parent element. It follows that top parent (the body element), must have values for all it's options. The `base_style()` constructor is a convenient constructor for a style with sensible defaults for all it's options.

Usage

```
style(
  family = NULL,
  weight = NULL,
  italic = NULL,
  width = NULL,
  features = NULL,
  size = NULL,
  color = NULL,
  lineheight = NULL,
  align = NULL,
  tracking = NULL,
  indent = NULL,
  hanging = NULL,
  margin = NULL,
  padding = NULL,
  background = NULL,
  border = NULL,
  border_size = NULL,
  border_radius = NULL,
```



```

    bullets = NULL,
    underline = NULL,
    strikethrough = NULL,
    baseline = NULL,
    img_asp = NULL
)

base_style(
  family = "",
  weight = "normal",
  italic = FALSE,
  width = "normal",
  features = systemfonts::font_feature(),
  size = 12,
  color = "black",
  lineheight = 1.6,
  align = "left",
  tracking = 0,
  indent = 0,
  hanging = 0,
  margin = trbl(0, 0, rem(1)),
  padding = trbl(0),
  background = NA,
  border = NA,
  border_size = trbl(0),
  border_radius = 0,
  bullets = marquee_bullets,
  underline = FALSE,
  strikethrough = FALSE,
  baseline = 0,
  img_asp = 1.65
)

```

Arguments

| | |
|----------|---|
| family | The name of the font family to use |
| weight | The font weight to use. Can either be a number (0, 100, 200, 300, 400, 500, 600, 700, 800, or 900) or a strings ("undefined", "thin", "ultralight", "light", "normal", "medium", "semibold", "bold", "ultrabold", or "heavy") |
| italic | Should the font be slanted |
| width | The font width to use. Can either be a number ("0", "1", "2", "3", "4", "5", "6", "7", "8", or "9") or strings ("undefined", "ultracondensed", "extracondensed", "condensed", "semicondensed", "normal", "semiexpanded", "expanded", "extraexpanded", or "ultraexpanded") |
| features | A font_feature object specifying any OpenType font features to apply to the font |
| size | The size of the font in points. Can be relative() or em() in which case it is based on the parent font size (for size these are equivalent) or rem() in which case it is based on the font size of the body element. |

| | |
|---------------|--|
| color | Is the color of the font |
| lineheight | The spacing between subsequent lines relative to the font size. Can be <code>relative()</code> in which case it is based on the parent lineheight. |
| align | The alignment within the text. One of "left", "center", "right", "justified-left", "justified-center", "justified-right", or "distributed" |
| tracking | Additional character spacing measured in 1/1000em. Can be <code>relative()</code> in which case it is based on the parent tracking. |
| indent | The indentation of the first line in a paragraph measured in points. Can be <code>relative()</code> in which case it is based on the parent indent, <code>em()</code> in which case it is based on the font size in this style, or <code>rem()</code> in which case it is based on the font size of the body element. |
| hanging | The indentation of all but the first line in a paragraph measured in points. Can be <code>relative()</code> in which case it is based on the parent hanging, <code>em()</code> in which case it is based on the font size in this style, or <code>rem()</code> in which case it is based on the font size of the body element. |
| margin | The margin around the element, given as a call to <code>trbl()</code> |
| padding | The padding around the element, given as a call to <code>trbl()</code> |
| background | The color of the background fill. The background includes the padding but not the margin. Can be a solid color or a gradient or pattern made with <code>grid::linearGradient()/grid::rad</code> |
| border | The color of the background stroke. The background includes the padding but not the margin |
| border_size | The line width of the background stroke, given as a call to <code>trbl()</code> |
| border_radius | The corner radius of the background, given in points |
| bullets | A vector of strings to use for bullets in unordered lists. <code>marquee_bullets</code> provides a selection |
| underline | Should text be underlined |
| strikethrough | Should text be strikethrough |
| baseline | The baseline shift to apply to the text |
| img_asp | The default aspect ratio for block level images if not provided by the image itself |

Value

A `marquee_style` object

Examples

```
# A partial style
style(color = "red", underline = TRUE)

# Full style
base_style()
```

Description

marquee provides a small set of helpers for constructing the needed styles. `relative()` specifies a numeric value as relative to the value of the parent style by a certain factor, e.g. a font size of `relative(0.5)` would give a style a font size half of its parent. `em()` specify a numeric value as relative to the font size of the current style. If the font size is 12, and indent is set to `em(2)`, then the indent will be equivalent to 24. `rem()` works like `em()` but rather than using the font size of the current style it uses the font size of the root style (which is the body element). `trbl()` helps you construct styles that refers to sides of a rectangle (margin, padding, and border size). The function names refers to the order of the arguments (top, right, bottom, left). `skip_inherit()` tells the style inheritance to ignore this value and look for the value one above in the stack. `marquee_bullets` is just a character vector with 6 sensible bullet glyphs for unordered lists.

Usage

```
relative(x)
```

```
em(x)
```

```
rem(x)
```

```
trbl(top = NULL, right = top, bottom = top, left = right)
```

```
skip_inherit(x)
```

```
marquee_bullets
```

Arguments

`x` A decimal number. If a vector is provided only the first element will be used

`top, right, bottom, left`

Values for the sides of the rectangles. Either numbers or modifiers (relative, em, or rem)

Format

An object of class character of length 6.

Value

Objects of the relevant class

Examples

```

relative(0.35)

em(2)

rem(1.2)

# Argument default means it recycles like CSS if fewer values are specified
trbl(6, em(1.5))

skip_inherit("sans")

marquee_bullets

```

style_set

Create or modify a style set that describes a full markdown text

Description

A style set contains information on how to style the various tags in a markdown text. While it is not necessary to provide a style for all tags (it will just inherit the parent if missing), it is required to provide a complete style for the body tag so an option is available through inheritance for all tags and all style options. It can often be easier to derive a new style set from an existing one rather than building one from scratch.

Usage

```

style_set(...)

modify_style(style_set, tag, ...)

remove_style(style_set, tag)

```

Arguments

| | |
|-----------|---|
| ... | Named arguments providing a style for the specific tags. For <code>modify_style()</code> a number of style options to change. If the first argument is a marquee style it will overwrite the tag and subsequent arguments are ignored |
| style_set | A style set to modify |
| tag | The name of a tag to modify or remove. Tags are internally all lowercase and tag will be converted to lowercase before matching |

Value

A `marquee_style_set` object

Examples

```
# Create a style
s_set <- style_set(base = base_style(), p = style(indent = em(2)))

# Modify an existing tag
modify_style(s_set, "p", size = 16)

# Add a new tag, supplying a full style object
modify_style(s_set, "str", style(weight = "bold"))

# Same as above, but style object created implicitly
modify_style(s_set, "str", weight = "bold")

# Remove a tag style
remove_style(s_set, "p")
```

Index

- * **datasets**
 - style-helpers, 19
- aes(), 6
- base_style, 2
- base_style (style), 16
- borders(), 7
- classic_style, 2, 7
- classic_style(), 11, 14
- element_marquee, 4
- element_marquee(), 7
- em (style-helpers), 19
- em(), 3, 15, 17, 18
- emptyenv(), 9
- font_feature, 3, 17
- fortify(), 6
- geom_marquee, 5
- ggplot(), 6
- key glyphs, 7
- layer position, 6
- layer stat, 6
- layer(), 6, 7
- marquee_bullets (style-helpers), 19
- marquee_glue, 8
- marquee_glue_data (marquee_glue), 8
- marquee_grob, 11
- marquee_grob(), 14
- marquee_parse, 13
- marquee_parse(), 11, 12
- modify_style (style_set), 20
- relative (style-helpers), 19
- relative(), 3, 15, 17, 18
- rem (style-helpers), 19
- rem(), 3, 15, 17, 18
- remove_style (style_set), 20
- skip_inherit (style-helpers), 19
- skip_inherit(), 4, 7
- style, 16
- style-helpers, 19
- style_set, 20
- trbl (style-helpers), 19
- trbl(), 3, 18
- trim(), 10