

Package ‘fdasrvf’

January 24, 2024

Type Package

Title Elastic Functional Data Analysis

Version 2.2.0

Date 2024-1-24

Description Performs alignment, PCA, and modeling of multidimensional and unidimensional functions using the square-root velocity framework (Srivastava et al., 2011 <[arXiv:1103.3817](https://arxiv.org/abs/1103.3817)> and Tucker et al., 2014 <[DOI:10.1016/j.csda.2012.12.001](https://doi.org/10.1016/j.csda.2012.12.001)>). This framework allows for elastic analysis of functional data through phase and amplitude separation.

License GPL-3

LazyData TRUE

Imports cli, coda, doParallel, fields, foreach, lpSolve, Matrix, mvtnorm, Rcpp, rlang, tolerance, viridisLite

Suggests covr, interp, plot3D, plot3Drgl, rgl, testthat (>= 3.0.0), withr

Depends R (>= 4.3.0),

RoxygenNote 7.3.0

Encoding UTF-8

Config/testthat.edition 3

LinkingTo Rcpp, RcppArmadillo

URL https://github.com/jdtuck/fdasrvf_R

BugReports https://github.com/jdtuck/fdasrvf_R/issues

NeedsCompilation yes

Author J. Derek Tucker [aut, cre] (<<https://orcid.org/0000-0001-8844-2169>>), Aymeric Stamm [ctb] (<<https://orcid.org/0000-0002-8725-3654>>)

Maintainer J. Derek Tucker <jdtuck@sandia.gov>

Repository CRAN

Date/Publication 2024-01-24 17:50:02 UTC

R topics documented:

align_fPCA	3
beta	5
bootTB	6
boxplot.fdawarp	7
calc_shape_dist	8
curve_depth	9
curve_geodesic	10
curve_karcher_cov	11
curve_karcher_mean	11
curve_pair_align	13
curve_principal_directions	14
curve_srvf_align	15
curve_to_q	16
elastic.depth	17
elastic.distance	18
elastic.logistic	19
elastic.lpcr.regression	20
elastic.mlogistic	21
elastic.mlpcr.regression	22
elastic.pcr.regression	24
elastic.prediction	25
elastic.regression	26
elastic_amp_change_ff	27
elastic_change_fPCA	28
elastic_ph_change_ff	30
fdasrvf	31
function_group_warp_bayes	32
function_mean_bayes	34
f_to_srvf	35
gam_to_v	36
gauss_model	36
gradient	37
growth_vel	38
horizFPCA	38
im	39
invertGamma	40
inv_exp_map	40
jointFPCA	41
joint_gauss_model	42
kmeans_align	43
LongRunCovMatrix	45
multiple_align_functions	46
multivariate_karcher_mean	47
optimum.reparam	48
outlier.detection	50
pair_align_functions	51

pair_align_functions_bayes	52
pair_align_functions_expomap	54
pair_align_image	56
pcaTB	57
predict.hfPCA	58
predict.jfpca	59
predict.lpcr	59
predict.mlpcr	60
predict.pcr	61
predict.vfpca	62
q_to_curve	62
reparam_curve	63
reparam_image	64
resamplecurve	65
rgam	66
sample_shapes	66
simu_data	67
simu_warp	68
simu_warp_median	68
smooth.data	69
SqrtMean	70
SqrtMeanInverse	71
SqrtMedian	71
srdf_to_f	72
time_warping	73
toy_data	75
toy_warp	76
vertFPCA	76
v_to_gam	77
warp_f_gamma	78
warp_q_gamma	79

Index

80

align_fPCA*Group-wise function alignment and PCA Extractions***Description**

This function aligns a collection of functions while extracting principal components.

Usage

```
align_fPCA(
  f,
  time,
  num_comp = 3L,
  showplot = TRUE,
```

```

smooth_data = FALSE,
sparam = 25L,
parallel = FALSE,
cores = NULL,
max_iter = 51L,
lambda = 0
)

```

Arguments

<code>f</code>	A numeric matrix of shape $M \times N$ specifying a sample of N 1-dimensional curves observed on a grid of size M .
<code>time</code>	A numeric vector of length M specifying the grid on which functions <code>f</code> have been evaluated.
<code>num_comp</code>	An integer value specifying the number of principal components to extract. Defaults to <code>3L</code> .
<code>showplot</code>	A boolean specifying whether to display plots along the way. Defaults to <code>TRUE</code> .
<code>smooth_data</code>	A boolean specifying whether to smooth data using box filter. Defaults to <code>FALSE</code> .
<code>sparam</code>	An integer value specifying the number of times to apply box filter. Defaults to <code>25L</code> . This argument is only used if <code>smooth_data == TRUE</code> .
<code>parallel</code>	A boolean specifying whether computations should run in parallel. Defaults to <code>FALSE</code> .
<code>cores</code>	An integer value specifying the number of cores to use for parallel computations. Defaults to <code>NULL</code> in which case it uses all available cores but one. This argument is only used when <code>parallel == TRUE</code> .
<code>max_iter</code>	An integer value specifying the maximum number of iterations. Defaults to <code>51L</code> .
<code>lambda</code>	A numeric value specifying the elasticity. Defaults to <code>0.0</code> .

Value

A list with the following components:

- `f0`: A numeric matrix of shape $M \times N$ storing the original functions;
- `fn`: A numeric matrix of the same shape as `f0` storing the aligned functions;
- `qn`: A numeric matrix of the same shape as `f0` storing the aligned SRSFs;
- `q0`: A numeric matrix of the same shape as `f0` storing the SRSFs of the original functions;
- `mqn`: A numeric vector of length M storing the mean SRSF;
- `gam`: A numeric matrix of the same shape as `f0` storing the estimated warping functions;
- `vfpca`: A list storing information about the vertical PCA with the following components:
 - `q_pca`: A numeric matrix of shape $(M + 1) \times 5 \times \text{num_comp}$ storing the first 3 principal directions in SRSF space; the first dimension is $M + 1$ because, in SRSF space, the original functions are represented by the SRSF and the initial value of the functions.
 - `f_pca`: A numeric matrix of shape $M \times 5 \times \text{num_comp}$ storing the first 3 principal directions in original space;

- latent: A numeric vector of length $M + 1$ storing the singular values of the SVD decomposition in SRSF space;
 - coef: A numeric matrix of shape $N \times \text{num_comp}$ storing the scores of the N original functions on the first num_comp principal components;
 - U: A numeric matrix of shape $(M + 1) \times (M + 1)$ storing the eigenvectors associated with the SVD decomposition in SRSF space.
- Dx: A numeric vector of length `max_iter` storing the value of the cost function at each iteration.

References

Tucker, J. D., Wu, W., Srivastava, A., Generative models for functional data using phase and amplitude separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
## Not run:  
out <- align_fPCA(simu_data$f, simu_data$time)  
  
## End(Not run)
```

beta

MPEG7 Curve Dataset

Description

Contains the MPEG7 curve data set.

Usage

beta

Format

beta:

An array of shape $2 \times 100 \times 65 \times 20$ storing a sample of 20 curves from R to R^2 distributed in 65 different classes, evaluated on a grid of size 100.

bootTB

*Tolerance Bound Calculation using Bootstrap Sampling***Description**

This function computes tolerance bounds for functional data containing phase and amplitude variation using bootstrap sampling

Usage

```
bootTB(f, time, a = 0.05, p = 0.99, B = 500, no = 5, Nsamp = 100, parallel = T)
```

Arguments

f	matrix of functions
time	vector describing time sampling
a	confidence level of tolerance bound (default = 0.05)
p	coverage level of tolerance bound (default = 0.99)
B	number of bootstrap samples (default = 500)
no	number of principal components (default = 5)
Nsamp	number of functions per bootstrap (default = 100)
parallel	enable parallel processing (default = T)

Value

Returns a list containing

amp	amplitude tolerance bounds
ph	phase tolerance bounds

References

- J. D. Tucker, J. R. Lewis, C. King, and S. Kurtek, “A Geometric Approach for Computing Tolerance Bounds for Elastic Functional Data,” Journal of Applied Statistics, 10.1080/02664763.2019.1645818, 2019.
- Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.
- Jung, S. L. a. S. (2016). "Combined Analysis of Amplitude and Phase Variations in Functional Data." arXiv:1603.01775.

Examples

```
## Not run:
out1 <- bootTB(simu_data$f, simu_data$time)

## End(Not run)
```

 boxplot.fdawarp *Functional Boxplot*

Description

This function computes the required statistics for building up a boxplot of the aligned functional data. Since the process of alignment provides separation of phase and amplitude variability, the computed boxplot can focus either on amplitude variability or phase variability.

Usage

```
## S3 method for class 'fdawarp'
boxplot(
  x,
  variability_type = c("amplitude", "phase"),
  alpha = 0.05,
  range = 1,
  what = c("plot", "stats", "plot+stats"),
  ...
)

## S3 method for class 'ampbox'
boxplot(x, ...)

## S3 method for class 'phbox'
boxplot(x, ...)
```

Arguments

- x** An object of class `fdawarp` typically produced by `time_warping()` or of class `ampbox` or `phbox` typically produced by `boxplot.fdawarp()`.
- variability_type** A string specifying which kind of variability should be displayed in the boxplot. Choices are "amplitude" or "phase". Defaults to "amplitude".
- alpha** A numeric value specifying the quantile value. Defaults to 0.05 which uses the 95% quantile.
- range** A positive numeric value specifying how far the plot whiskers extend out from the box. The whiskers extend to the most extreme data point which is no more than `range` times the interquartile range from the box. Defaults to 1.0.
- what** A string specifying what the function should return. Choices are "plot", "stats" or "plot+stats". Defaults to "plot".
- ...** Unused here.

Details

The function `boxplot.fda.warp()` returns optionally an object of class either `ampbox` if `variability_type = "amplitude"` or `phbox` if `variability_type = "phase"`. S3 methods specialized for objects of these classes are provided as well to avoid re-computation of the boxplot statistics.

Value

If `what` contains `stats`, a list containing the computed statistics necessary for drawing the boxplot. Otherwise, the function simply draws the boxplot and no object is returned.

Examples

```
## Not run:
out <- time_warping(simu_data$f, simu_data$time)
boxplot(out, what = "stats")

## End(Not run)
```

calc_shape_dist *Elastic Shape Distance*

Description

Calculate elastic shape distance between two curves `beta1` and `beta2`. If the curves `beta1` and `beta2` are describing multidimensional functional data, then `rotation == FALSE` and `mode == '0'`

Usage

```
calc_shape_dist(
  beta1,
  beta2,
  mode = "0",
  rotation = TRUE,
  scale = TRUE,
  include.length = FALSE
)
```

Arguments

<code>beta1</code>	curve1, provided as a matrix of sizes $n \times T$ for n -dimensional curve on T sample points
<code>beta2</code>	curve 2, provided as a matrix of sizes $n \times T$ for n -dimensional curve on T sample points
<code>mode</code>	Open ("0") or Closed ("C") curves
<code>rotation</code>	Include rotation (default = TRUE)
<code>scale</code>	scale curves to unit length (default = TRUE)
<code>include.length</code>	include length in distance calculation (default = FALSE) this only applies if scale=TRUE

Value

Returns a list containing

d	geodesic distance
dx	phase distance
q1	srdf of curve 1
q2n	srdf of aligned curve 2

References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 33 (7), 1415-1428.

Kurtek, S., Srivastava, A., Klassen, E., and Ding, Z. (2012), “Statistical Modeling of Curves Using Shapes and Related Features,” *Journal of the American Statistical Association*, 107, 1152–1165.

Examples

```
out <- calc_shape_dist(beta[, , 1, 1], beta[, , 1, 4])
```

curve_depth

Calculates elastic depth for a set of curves

Description

This functions calculates the elastic depth between set of curves. If the curves are describing multidimensional functional data, then `rotated == FALSE` and `mode == '0'`

Usage

```
curve_depth(beta, mode = "0", rotated = TRUE, scale = TRUE, parallel = FALSE)
```

Arguments

beta	Array of sizes $n \times T \times N$ for N curves of dimension n evaluated on a grid of T points
mode	Open ("0") or Closed ("C") curves
rotated	Include rotation (default = TRUE)
scale	scale curves to unit length (default = TRUE)
parallel	run computation in parallel (default = TRUE)

Value

Returns a list containing

amp	amplitude depth
phase	phase depth

References

T. Harris, J. D. Tucker, B. Li, and L. Shand, "Elastic depths for detecting shape anomalies in functional data," *Technometrics*, 10.1080/00401706.2020.1811156, 2020.

Examples

```
data("mpeg7")
# note: use more shapes and iterations, small for speed
out = curve_depth(beta[, , 1:2])
```

<code>curve_geodesic</code>	<i>Form geodesic between two curves</i>
-----------------------------	---

Description

Form geodesic between two curves using Elastic Method

Usage

```
curve_geodesic(beta1, beta2, k = 5)
```

Arguments

<code>beta1</code>	curve 1, provided as a matrix of dimensions $n \times T$ for n -dimensional curve evaluated on T sample points
<code>beta2</code>	curve 2, provided as a matrix of dimensions $n \times T$ for n -dimensional curve evaluated on T sample points
<code>k</code>	number of curves along geodesic (default 5)

Value

a list containing	
<code>geod</code>	curves along geodesic (n, T, k)
<code>geod_q</code>	srfv's along geodesic

References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 33 (7), 1415-1428.

Examples

```
out <- curve_geodesic(beta[, , 1, 1], beta[, , 1, 5])
```

<code>curve_karcher_cov</code>	<i>Curve Karcher Covariance</i>
--------------------------------	---------------------------------

Description

Calculate Karcher Covariance of a set of curves

Usage

```
curve_karcher_cov(v, len = NA)
```

Arguments

<code>v</code>	array of sizes $n \times T \times N$ for N shooting vectors of dimension n evaluated on a grid of T points
<code>len</code>	lengths of curves (default = NA)

Value

K covariance matrix

References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 33 (7), 1415-1428.

Examples

```
out <- curve_karcher_mean(beta[, , 1, 1:2], maxit = 2)
# note: use more shapes, small for speed
K <- curve_karcher_cov(out$v)
```

<code>curve_karcher_mean</code>	<i>Karcher Mean of Curves</i>
---------------------------------	-------------------------------

Description

Calculates Karcher mean or median of a collection of curves using the elastic square-root velocity (srvf) framework.

Usage

```
curve_karcher_mean(
  beta,
  mode = "0",
  rotated = TRUE,
  scale = TRUE,
  lambda = 0,
  maxit = 20,
  ms = "mean"
)
```

Arguments

<code>beta</code>	Array of sizes $n \times T \times N$ describing N curves of dimension n evaluated on T points
<code>mode</code>	Open ("0") or Closed ("C") curves
<code>rotated</code>	Optimize over rotation (default = TRUE)
<code>scale</code>	scale curves to unit length (default = TRUE)
<code>lambda</code>	A numeric value specifying the elasticity. Defaults to 0.0.
<code>maxit</code>	maximum number of iterations
<code>ms</code>	string defining whether the Karcher mean ("mean") or Karcher median ("median") is returned (default = "mean")

Value

Returns a list containing

<code>mu</code>	mean srvf
<code>beta</code>	centered data
<code>betamean</code>	mean or median curve
<code>type</code>	string indicating whether mean or median is returned
<code>v</code>	shooting vectors
<code>q</code>	array of srvfs
<code>gam</code>	array of warping functions
<code>cent</code>	centers of original curves
<code>len</code>	length of curves
<code>len_q</code>	length of srvfs
<code>mean_scale</code>	mean length
<code>mean_scale_q</code>	mean length srvf
<code>E</code>	energy
<code>qun</code>	cost function

References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 33 (7), 1415-1428.

Examples

```
out <- curve_karcher_mean(beta[, , 1, 1:2], maxit = 2)
# note: use more shapes, small for speed
```

`curve_pair_align` *Pairwise align two curves*

Description

This function aligns to curves using Elastic Framework

Usage

```
curve_pair_align(beta1, beta2, mode = "0", rotation = TRUE, scale = TRUE)
```

Arguments

<code>beta1</code>	curve 1, provided as a matrix of dimensions $n \times T$ for n -dimensional curve evaluated on T sample points
<code>beta2</code>	curve 2, provided as a matrix of dimensions $n \times T$ for n -dimensional curve evaluated on T sample points
<code>mode</code>	Open ("0") or Closed ("C") curves
<code>rotation</code>	Include rotation (default = TRUE)
<code>scale</code>	scale curves to unit length (default = TRUE)

Value

a list containing

<code>beta2n</code>	aligned curve 2 to 1
<code>q2n</code>	aligned srvf 2 to 1
<code>gam</code>	warping function
<code>q1</code>	srvf of curve 1
<code>beta1</code>	centered curve 1
<code>beta2</code>	centered curve 2
<code>R</code>	rotation matrix
<code>tau</code>	seed

References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

Examples

```
out <- curve_pair_align(beta[, , 1, 1], beta[, , 1, 5])
```

curve_principal_directions
Curve PCA

Description

Calculate principal directions of a set of curves

Usage

```
curve_principal_directions(v, K, mu, len = NA, no = 3, N = 5, mode = "O")
```

Arguments

v	array of sizes $n \times T \times N1$ for $N1$ shooting vectors of dimension n evaluated on a grid of T points
K	matrix of sizes $nT \times nT$ of covariance matrix
mu	matrix of sizes $n \times T$ of mean srvf
len	length of original curves (default = NA)
no	number of components
N	number of samples on each side of mean
mode	Open ("O") or Closed ("C") curves

Value

Returns a list containing

s	singular values
U	singular vectors
coef	principal coefficients
pd	principal directions

References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

Examples

```
out <- curve_karcher_mean(beta[, , 1, 1:2], maxit = 2)
# note: use more shapes, small for speed
K <- curve_karcher_cov(out$v)
out <- curve_principal_directions(out$v, K, out$mu)
```

curve_srvf_align Align Curves

Description

Aligns a collection of curves using the elastic square-root velocity (srvf) framework. If the curves are describing multidimensional functional data, then `rotated == FALSE` and `mode == '0'`

Usage

```
curve_srvf_align(
  beta,
  mode = "0",
  rotated = TRUE,
  scale = FALSE,
  lambda = 0,
  maxit = 20,
  ms = "mean"
)
```

Arguments

<code>beta</code>	Array of sizes $n \times T \times N$ for N curves of dimension n evaluated on a grid of T points
<code>mode</code>	Open ("0") or Closed ("C") curves
<code>rotated</code>	Optimize over rotation (default = TRUE)
<code>scale</code>	Include scale (default = FALSE)
<code>lambda</code>	A numeric value specifying the elasticity. Defaults to 0.0.
<code>maxit</code>	maximum number of iterations
<code>ms</code>	string defining whether the Karcher mean ("mean") or Karcher median ("median") is returned (default = "mean")

Value

Returns a list containing

<code>betan</code>	aligned curves
<code>qn</code>	aligned srvfs
<code>betamean</code>	mean curve
<code>q_mu</code>	mean SRVFs

References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

Examples

```
data("mpeg7")
# note: use more shapes and iterations, small for speed
out = curve_srvf_align(beta[,,1:2],maxit=2)
```

curve_to_q

Convert to SRVF space

Description

This function converts curves or multidimesional functional data to SRVF

Usage

```
curve_to_q(beta, scale = TRUE)
```

Arguments

beta	either a matrix of shape $n \times T$ describing curve or multidimensional functional data in R^n , where n is the dimension and T is the number of time points
scale	scale curve to unit length (default = TRUE)

Value

a numeric array of the same shape as the input array beta storing the SRVFs of the original curves.

References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and M achine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

Examples

```
q <- curve_to_q(beta[, , 1])$q
```

elastic.depth	<i>Calculates elastic depth</i>
---------------	---------------------------------

Description

This function calculates the elastic depth between set of functions in R^1

Usage

```
elastic.depth(f, time, lambda = 0, pen = "roughness", parallel = FALSE)
```

Arguments

f	matrix of sizes $M \times N$, specifying values of N function of M time points
time	vector of length M , specifying the sample points of functions
lambda	controls amount of warping (default = 0)
pen	alignment penalty (default = "roughness") options are second derivative ("roughness"), geodesic distance from id ("geodesic"), and norm from id ("norm")
parallel	run computation in parallel (default = TRUE)

Value

Returns a list containing

amp	amplitude depth
phase	phase depth

References

T. Harris, J. D. Tucker, B. Li, and L. Shand, "Elastic depths for detecting shape anomalies in functional data," *Technometrics*, 10.1080/00401706.2020.1811156, 2020.

Examples

```
depths <- elastic.depth(simu_data$f[, 1:4], simu_data$time)
```

elastic.distance *Calculates two elastic distance*

Description

This functions calculates the distances between functions in R^1 D_y and D_x , where function 1 is aligned to function 2

Usage

```
elastic.distance(f1, f2, time, lambda = 0, pen = "roughness")
```

Arguments

f1	sample function 1, provided as a vector of length M
f2	sample function 2, provided as a vector of length M
time	sample points of functions, provided as a vector of length M
lambda	controls amount of warping (default = 0)
pen	alignment penalty (default = "roughness") options are second derivative ("roughness"), geodesic distance from id ("geodesic"), and norm from id ("norm")

Value

Returns a list containing

Dy	amplitude distance
Dx	phase distance

References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
distancess <- elastic.distance(
  f1 = simu_data$f[, 1],
  f2 = simu_data$f[, 2],
  time = simu_data$time
)
```

 elastic.logistic *Elastic Logistic Regression*

Description

This function identifies a logistic regression model with phase-variability using elastic methods

Usage

```
elastic.logistic(
  f,
  y,
  time,
  B = NULL,
  df = 20,
  max_itr = 20,
  smooth_data = FALSE,
  sparam = 25,
  parallel = FALSE,
  cores = 2
)
```

Arguments

<code>f</code>	matrix ($N \times M$) of M functions with N samples
<code>y</code>	vector of size M labels (1/-1)
<code>time</code>	vector of size N describing the sample points
<code>B</code>	matrix defining basis functions (default = NULL)
<code>df</code>	scalar controlling degrees of freedom if <code>B=NULL</code> (default=20)
<code>max_itr</code>	scalar number of iterations (default=20)
<code>smooth_data</code>	smooth data using box filter (default = F)
<code>sparam</code>	number of times to apply box filter (default = 25)
<code>parallel</code>	enable parallel mode using <code>foreach()</code> and <code>doParallel</code> package
<code>cores</code>	set number of cores to use with <code>doParallel</code> (default = 2)

Value

Returns a list containing

<code>alpha</code>	model intercept
<code>beta</code>	regressor function
<code>fn</code>	aligned functions - matrix ($N \times M$) of M functions with N samples
<code>qn</code>	aligned svrfs - similar structure to <code>fn</code>

gamma	warping functions - similar structure to fn
q	original srvf - similar structure to fn
B	basis matrix
b	basis coefficients
Loss	logistic loss
type	model type ('logistic')

References

Tucker, J. D., Wu, W., Srivastava, A., Elastic Functional Logistic Regression with Application to Physiological Signal Classification, Electronic Journal of Statistics (2014), submitted.

elastic.lpcr.regression

Elastic logistic Principal Component Regression

Description

This function identifies a logistic regression model with phase-variability using elastic pca

Usage

```
elastic.lpcr.regression(
  f,
  y,
  time,
  pca.method = "combined",
  no = 5,
  smooth_data = FALSE,
  sparam = 25
)
```

Arguments

f	matrix ($N \times M$) of M functions with N samples
y	vector of size M labels
time	vector of size N describing the sample points
pca.method	string specifying pca method (options = "combined", "vert", or "horiz", default = "combined")
no	scalar specify number of principal components (default=5)
smooth_data	smooth data using box filter (default = F)
sparam	number of times to apply box filter (default = 25)

Value

Returns a lpcr object containing

alpha	model intercept
b	regressor vector
y	label vector
warp_data	fdawarp object of aligned data
pca	pca object of principal components
Loss	logistic loss
pca.method	string specifying pca method used

References

J. D. Tucker, J. R. Lewis, and A. Srivastava, “Elastic Functional Principal Component Regression,” Statistical Analysis and Data Mining, 10.1002/sam.11399, 2018.

elastic.mlogistic *Elastic Multinomial Logistic Regression*

Description

This function identifies a multinomial logistic regression model with phase-variability using elastic methods

Usage

```
elastic.mlogistic(
  f,
  y,
  time,
  B = NULL,
  df = 20,
  max_itr = 20,
  smooth_data = FALSE,
  sparam = 25,
  parallel = FALSE,
  cores = 2
)
```

Arguments

f	matrix ($N \times M$) of M functions with N samples
y	vector of size M labels (1,2,...,m) for m classes
time	vector of size N describing the sample points

B	matrix defining basis functions (default = NULL)
df	scalar controlling degrees of freedom if B=NULL (default=20)
max_itr	scalar number of iterations (default=20)
smooth_data	smooth data using box filter (default = F)
sparam	number of times to apply box filter (default = 25)
parallel	enable parallel mode using <code>foreach()</code> and <code>doParallel</code> package
cores	set number of cores to use with <code>doParallel</code> (default = 2)

Value

Returns a list containing

alpha	model intercept
beta	regressor function
fn	aligned functions - matrix ($N \times M$) of M functions with N samples
qn	aligned srvfs - similar structure to fn
gamma	warping functions - similar structure to fn
q	original srdf - similar structure to fn
B	basis matrix
b	basis coefficients
Loss	logistic loss
type	model type ('mlogistic')

References

Tucker, J. D., Wu, W., Srivastava, A., Elastic Functional Logistic Regression with Application to Physiological Signal Classification, Electronic Journal of Statistics (2014), submitted.

Description

This function identifies a multinomial logistic regression model with phase-variability using elastic pca

Usage

```
elastic.mlpcr.regression(
  f,
  y,
  time,
  pca.method = "combined",
  no = 5,
  smooth_data = FALSE,
  sparam = 25
)
```

Arguments

f	matrix ($N \times M$) of M functions with N samples
y	vector of size M labels
time	vector of size N describing the sample points
pca.method	string specifying pca method (options = "combined", "vert", or "horiz", default = "combined")
no	scalar specify number of principal components (default=5)
smooth_data	smooth data using box filter (default = F)
sparam	number of times to apply box filter (default = 25)

Value

Returns a mlpcr object containing

alpha	model intercept
b	regressor vector
y	label vector
Y	Coded labels
warp_data	fdawarp object of aligned data
pca	pca object of principal components
Loss	logistic loss
pca.method	string specifying pca method used

References

J. D. Tucker, J. R. Lewis, and A. Srivastava, “Elastic Functional Principal Component Regression,” Statistical Analysis and Data Mining, 10.1002/sam.11399, 2018.

elastic.pcr.regression*Elastic Linear Principal Component Regression*

Description

This function identifies a regression model with phase-variability using elastic pca

Usage

```
elastic.pcr.regression(
  f,
  y,
  time,
  pca.method = "combined",
  no = 5,
  smooth_data = FALSE,
  sparam = 25,
  parallel = F,
  C = NULL
)
```

Arguments

<i>f</i>	matrix ($N \times M$) of M functions with N samples
<i>y</i>	vector of size M responses
<i>time</i>	vector of size N describing the sample points
<i>pca.method</i>	string specifying pca method (options = "combined", "vert", or "horiz", default = "combined")
<i>no</i>	scalar specify number of principal components (default = 5)
<i>smooth_data</i>	smooth data using box filter (default = F)
<i>sparam</i>	number of times to apply box filter (default = 25)
<i>parallel</i>	run in parallel (default = F)
<i>C</i>	scale balance parameter for combined method (default = NULL)

Value

Returns a pcr object containing

<i>alpha</i>	model intercept
<i>b</i>	regressor vector
<i>y</i>	response vector
<i>warp_data</i>	fdawarp object of aligned data
<i>pca</i>	pca object of principal components
<i>SSE</i>	sum of squared errors
<i>pca.method</i>	string specifying pca method used

References

J. D. Tucker, J. R. Lewis, and A. Srivastava, “Elastic Functional Principal Component Regression,” Statistical Analysis and Data Mining, 10.1002/sam.11399, 2018.

elastic.prediction *Elastic Prediction from Regression Models*

Description

This function performs prediction from an elastic regression model with phase-variability

Usage

```
elastic.prediction(f, time, model, y = NULL, smooth_data = FALSE, sparam = 25)
```

Arguments

f	matrix ($N \times M$) of M functions with N samples
time	vector of size N describing the sample points
model	list describing model from elastic regression methods
y	responses of test matrix f (default=NULL)
smooth_data	smooth data using box filter (default = F)
sparam	number of times to apply box filter (default = 25)

Value

Returns a list containing

y_pred	predicted values of f or probabilities depending on model
SSE	sum of squared errors if linear
y_labels	labels if logistic model
PC	probability of classification if logistic

References

Tucker, J. D., Wu, W., Srivastava, A., Elastic Functional Logistic Regression with Application to Physiological Signal Classification, Electronic Journal of Statistics (2014), submitted.

elastic.regression *Elastic Linear Regression*

Description

This function identifies a regression model with phase-variability using elastic methods

Usage

```
elastic.regression(
  f,
  y,
  time,
  B = NULL,
  lam = 0,
  df = 20,
  max_itr = 20,
  smooth_data = FALSE,
  sparam = 25,
  parallel = FALSE,
  cores = 2
)
```

Arguments

<code>f</code>	matrix ($N \times M$) of M functions with N samples
<code>y</code>	vector of size M responses
<code>time</code>	vector of size N describing the sample points
<code>B</code>	matrix defining basis functions (default = NULL)
<code>lam</code>	scalar regularization parameter (default=0)
<code>df</code>	scalar controlling degrees of freedom if B=NULL (default=20)
<code>max_itr</code>	scalar number of iterations (default=20)
<code>smooth_data</code>	smooth data using box filter (default = F)
<code>sparam</code>	number of times to apply box filter (default = 25)
<code>parallel</code>	enable parallel mode using <code>foreach()</code> and <code>doParallel</code> package
<code>cores</code>	set number of cores to use with <code>doParallel</code> (default = 2)

Value

Returns a list containing

<code>alpha</code>	model intercept
<code>beta</code>	regressor function
<code>fn</code>	aligned functions - matrix ($N \times M$) of M functions with N samples

qn	aligned srvfs - similar structure to fn
gamma	warping functions - similar structure to fn
q	original srsvf - similar structure to fn
B	basis matrix
b	basis coefficients
SSE	sum of squared errors
type	model type ('linear')

References

Tucker, J. D., Wu, W., Srivastava, A., Elastic Functional Logistic Regression with Application to Physiological Signal Classification, Electronic Journal of Statistics (2014), submitted.

elastic_amp_change_ff *Elastic Amplitude Changepoint Detection*

Description

This function identifies a amplitude changepoint using a fully functional approach

Usage

```
elastic_amp_change_ff(
  f,
  time,
  d = 1000,
  h = 0,
  smooth_data = FALSE,
  sparam = 25,
  showplot = TRUE
)
```

Arguments

f	matrix ($N \times M$) of M functions with N samples
time	vector of size N describing the sample points
d	number of monte carlo iterations of Brownian Bridge (default = 1000)
h	window selection of long range covariance function (default = 0)
smooth_data	smooth data using box filter (default = F)
sparam	number of times to apply box filter (default = 25)
showplot	show results plots (default = T)

Value

Returns a list object containing

pvalue	p value
change	indice of changepoint
DataBefore	functions before changepoint
DataAfter	functions after changepoint
MeanBefore	mean function before changepoint
MeanAfter	mean function after changepoint
WarpingBefore	warping functions before changepoint
WarpingAfter	warping functions after changepoint
WarpingMeanBefore	mean warping function before changepoint
WarpingMeanAfter	mean warping function after changepoint
change_fun	amplitude change function
Sn	test statistic values
mu	mean srsfs
mu_f	mean functions

References

J. D. Tucker and D. Yarger, “Elastic Functional Changepoint Detection of Climate Impacts from Localized Sources”, Envirometrics, 10.1002/env.2826, 2023.

elastic_change_fpca *Elastic Changepoint Detection*

Description

This function identifies changepoints using a functional PCA

Usage

```
elastic_change_fpca(
  f,
  time,
  pca.method = "combined",
  pc = 0.95,
  d = 1000,
  n_pcs = 5,
  smooth_data = FALSE,
  sparam = 25,
  showplot = TRUE
)
```

Arguments

<code>f</code>	matrix ($N \times M$) of M functions with N samples
<code>time</code>	vector of size N describing the sample points
<code>pca.method</code>	string specifying pca method (options = "combined", "vert", or "horiz", default = "combined")
<code>pc</code>	percentage of cummulation explained variance (default = 0.95)
<code>d</code>	number of monte carlo iterations of Brownian Bridge (default = 1000)
<code>n_pcs</code>	scalar specify number of principal components (default = 5)
<code>smooth_data</code>	smooth data using box filter (default = F)
<code>sparam</code>	number of times to apply box filter (default = 25)
<code>showplot</code>	show results plots (default = T)

Value

Returns a list object containing

<code>pvalue</code>	p value
<code>change</code>	indice of changepoint
<code>DataBefore</code>	functions before changepoint
<code>DataAfter</code>	functions after changepoint
<code>MeanBefore</code>	mean function before changepoint
<code>MeanAfter</code>	mean function after changepoint
<code>WarpingBefore</code>	warping functions before changepoint
<code>WarpingAfter</code>	warping functions after changepoint
<code>WarpingMeanBefore</code>	mean warping function before changepoint
<code>WarpingMeanAfter</code>	mean warping function after changepoint
<code>change_fun</code>	amplitude change function
<code>Sn</code>	test statistic values

References

J. D. Tucker and D. Yarger, “Elastic Functional Changepoint Detection of Climate Impacts from Localized Sources”, Envirometrics, 10.1002/env.2826, 2023.

elastic_ph_change_ff Elastic Phase Changepoint Detection

Description

This function identifies a phase changepoint using a fully functional approach

Usage

```
elastic_ph_change_ff(
  f,
  time,
  d = 1000,
  h = 0,
  smooth_data = FALSE,
  sparam = 25,
  showplot = TRUE
)
```

Arguments

f	matrix ($N \times M$) of M functions with N samples
time	vector of size N describing the sample points
d	number of monte carlo iterations of Brownian Bridge (default = 1000)
h	window selection of long range covariance function (default = 0)
smooth_data	smooth data using box filter (default = F)
sparam	number of times to apply box filter (default = 25)
showplot	show results plots (default = T)

Value

Returns a list object containing

pvalue	p value
change	indice of changepoint
DataBefore	functions before changepoint
DataAfter	functions after changepoint
MeanBefore	mean function before changepoint
MeanAfter	mean function after changepoint
WarpingBefore	warping functions before changepoint
WarpingAfter	warping functions after changepoint
WarpingMeanBefore	mean warping function before changepoint

WarpingMeanAfter	mean warping function after changepoint
change_fun	amplitude change function
Sn	test statistic values
mu	mean shooting vectors

References

J. D. Tucker and D. Yarger, “Elastic Functional Changepoint Detection of Climate Impacts from Localized Sources”, *Environmetrics*, 10.1002/env.2826, 2023.

Description

A library for functional data analysis using the square root velocity framework which performs pair-wise and group-wise alignment as well as modeling using functional component analysis.

Author(s)

Maintainer: J. Derek Tucker <jdtuck@sandia.gov> ([ORCID](#))

Other contributors:

- Aymeric Stamm <aymeric.stamm@math.cnrs.fr> ([ORCID](#)) [contributor]

References

- Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using Fisher-Rao metric, arXiv:1103.3817v2.
- Tucker, J. D., Wu, W., Srivastava, A., Generative models for functional data using phase and amplitude separation, *Computational Statistics and Data Analysis* (2012), 10.1016/j.csda.2012.12.001.
- J. D. Tucker, W. Wu, and A. Srivastava, Phase-amplitude separation of proteomics data using extended Fisher-Rao metric, *Electronic Journal of Statistics*, Vol 8, no. 2. pp 1724-1733, 2014.
- J. D. Tucker, W. Wu, and A. Srivastava, “Analysis of signals under compositional noise with applications to SONAR data,” *IEEE Journal of Oceanic Engineering*, Vol 29, no. 2. pp 318-330, Apr 2014.
- Tucker, J. D. 2014, Functional Component Analysis and Regression using Elastic Methods. Ph.D. Thesis, Florida State University.
- Robinson, D. T. 2012, Function Data Analysis and Partial Shape Matching in the Square Root Velocity Framework. Ph.D. Thesis, Florida State University.
- Kurtek, S., Srivastava, A., Klassen, E., and Ding, Z. (2012), “Statistical Modeling of Curves Using Shapes and Related Features,” *Journal of the American Statistical Association*, 107, 1152–1165.
- Huang, W. 2014, Optimization Algorithms on Riemannian Manifolds with Applications. Ph.D. Thesis, Florida State University.

- Cheng, W., Dryden, I. L., and Huang, X. (2016). Bayesian registration of functions and curves. *Bayesian Analysis*, 11(2), 447-475.
- Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 33 (7), 1415-1428.
- Cheng, W., Dryden, I. L., and Huang, X. (2016). Bayesian registration of functions and curves. *Bayesian Analysis*, 11(2), 447-475.
- W. Xie, S. Kurtek, K. Bharath, and Y. Sun, A geometric approach to visualization of variability in functional data, *Journal of American Statistical Association* 112 (2017), pp. 979-993.
- Lu, Y., R. Herbei, and S. Kurtek, 2017: Bayesian registration of functions with a Gaussian process prior. *Journal of Computational and Graphical Statistics*, 26, no. 4, 894–904.
- Lee, S. and S. Jung, 2017: Combined analysis of amplitude and phase variations in functional data. arXiv:1603.01775, 1–21.
- J. D. Tucker, J. R. Lewis, and A. Srivastava, “Elastic Functional Principal Component Regression,” *Statistical Analysis and Data Mining*, vol. 12, no. 2, pp. 101-115, 2019.
- J. D. Tucker, J. R. Lewis, C. King, and S. Kurtek, “A Geometric Approach for Computing Tolerance Bounds for Elastic Functional Data,” *Journal of Applied Statistics*, 10.1080/02664763.2019.1645818, 2019.
- T. Harris, J. D. Tucker, B. Li, and L. Shand, "Elastic depths for detecting shape anomalies in functional data," *Technometrics*, 10.1080/00401706.2020.1811156, 2020.
- J. D. Tucker and D. Yarger, “Elastic Functional Changepoint Detection of Climate Impacts from Localized Sources”, *Environmetrics*, 10.1002/env.2826, 2023.

See Also

Useful links:

- https://github.com/jdtuck/fdasrvf_R
- Report bugs at https://github.com/jdtuck/fdasrvf_R/issues

function_group_warp_bayes
Bayesian Group Warping

Description

This function aligns a set of functions using Bayesian SRSF framework

Usage

```
function_group_warp_bayes(
  f,
  time,
  iter = 50000,
  powera = 1,
  times = 5,
  tau = ceiling(times * 0.04),
  gp = seq(dim(f)[2]),
  showplot = TRUE
)
```

Arguments

f	matrix ($N \times M$) of M functions with N samples
time	sample points of functions
iter	number of iterations (default = 150000)
powera	Dirichlet prior parameter (default 1)
times	factor of length of subsample points to look at (default = 5)
tau	standard deviation of Normal prior for increment (default ceil(times*.4))
gp	number of colors in plots (defaults seq(dim(f)[2]))
showplot	shows plots of functions (default = T)

Value

Returns a list containing

f0	original functions
f_q	f aligned quotient space
gam_q	warping functions quotient space
f_a	f aligned ambient space
gam_a	warping ambient space
qmn	mean srsf

References

Cheng, W., Dryden, I. L., and Huang, X. (2016). Bayesian registration of functions and curves. *Bayesian Analysis*, 11(2), 447-475.

Examples

```
## Not run:
out <- function_group_warp_bayes(simu_data$f, simu_data$time)

## End(Not run)
```

function_mean_bayes *Bayesian Karcher Mean Calculation*

Description

This function calculates karcher mean of functions using Bayesian method

Usage

```
function_mean_bayes(f, time, times = 5, group = 1:dim(f)[2], showplot = TRUE)
```

Arguments

<i>f</i>	matrix ($N \times M$) of M functions with N samples
<i>time</i>	sample points of functions
<i>times</i>	factor of length of subsample points to look at (default = 5)
<i>group</i>	(defaults 1:dim(<i>f</i>)[2])
<i>showplot</i>	shows plots of functions (default = T)

Value

Returns a list containing

<i>distfamily</i>	dist matrix
<i>match.matrix</i>	matrix of warping functions
<i>position</i>	position
<i>mu_5</i>	function mean
<i>rtmatrix</i>	rtmatrix
<i>sumdist</i>	sumdist
<i>qt.fitted</i>	aligned srsf functions
<i>estimator</i>	estimator
<i>estimator2</i>	estimator2
<i>regfuncs</i>	registered functions

References

Cheng, W., Dryden, I. L., and Huang, X. (2016). Bayesian registration of functions and curves. *Bayesian Analysis*, 11(2), 447-475.

Examples

```
## Not run:
out <- function_mean_bayes(simu_data$f, simu_data$time)

## End(Not run)
```

f_to_srvf*Transformation to SRVF Space*

Description

This function transforms functions in R^1 from their original functional space to the SRVF space.

Usage

```
f_to_srvf(f, time)
```

Arguments

<code>f</code>	Either a numeric vector or a numeric matrix or a numeric array specifying the functions that need to be transformed. <ul style="list-style-type: none"> • If a vector, it must be of shape M and it is interpreted as a single 1-dimensional curve observed on a grid of size M. • If a matrix, it must be of shape $M \times N$. In this case, it is interpreted as a sample of N curves observed on a grid of size M, unless $M = 1$ in which case it is interpreted as a single 1-dimensional curve observed on a grid of size M.
<code>time</code>	A numeric vector of length M specifying the grid on which the functions are evaluated.

Value

A numeric array of the same shape as the input array `f` storing the SRVFs of the original curves.

References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using Fisher-Rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative models for functional data using phase and amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
q <- f_to_srvf(simu_data$f, simu_data$time)
```

<code>gam_to_v</code>	<i>map warping function to tangent space at identity</i>
-----------------------	--

Description

map warping function to tangent space at identity

Usage

```
gam_to_v(gam, smooth = TRUE)
```

Arguments

<code>gam</code>	Either a numeric vector or a numeric matrix or a numeric array specifying the warping functions
<code>smooth</code>	Apply smoothing before gradient

Value

A numeric array of the same shape as the input array `gamma` storing the shooting vectors of `gamma` obtained via finite differences.

<code>gauss_model</code>	<i>Gaussian model of functional data</i>
--------------------------	--

Description

This function models the functional data using a Gaussian model extracted from the principal components of the srvfs

Usage

```
gauss_model(warp_data, n = 1, sort_samples = FALSE)
```

Arguments

<code>warp_data</code>	fdawarp object from time_warping of aligned data
<code>n</code>	number of random samples (<code>n = 1</code>)
<code>sort_samples</code>	sort samples (default = F)

Value

Returns a fdawarp object containing

<code>fs</code>	random aligned samples
<code>gams</code>	random warping function samples
<code>ft</code>	random function samples

References

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
out1 <- gauss_model(simu_warp, n = 10)
```

gradient

Gradient using finite differences

Description

This function computes the gradient of f using finite differences.

Usage

```
gradient(f, binsize, multidimensional = FALSE)
```

Arguments

f Either a numeric vector of a numeric matrix or a numeric array specifying the curve(s) that need to be differentiated.

- If a vector, it must be of shape M and it is interpreted as a single 1-dimensional curve observed on a grid of size M .
- If a matrix and `multidimensional == FALSE`, it must be of shape $M \times N$. In this case, it is interpreted as a sample of N curves observed on a grid of size M , unless $M = 1$ in which case it is interpreted as a single 1-dimensional curve observed on a grid of size M .
- If a matrix and `multidimensional == TRUE`, it must be of shape $L \times M$ and it is interpreted as a single L -dimensional curve observed on a grid of size M .
- If a 3D array, it must be of shape $L \times M \times N$ and it is interpreted as a sample of N L -dimensional curves observed on a grid of size M .

binsize A numeric value specifying the size of the bins for computing finite differences.

multidimensional

A boolean specifying if the curves are multi-dimensional. This is useful when f is provided as a matrix to determine whether it is a single multi-dimensional curve or a collection of uni-dimensional curves. Defaults to FALSE.

Value

A numeric array of the same shape as the input array f storing the gradient of f obtained via finite differences.

Examples

```
out <- gradient(simu_data$f[, 1], mean(diff(simu_data$time)))
```

growth_vel*Berkeley Growth Velocity Dataset***Description**

Combination of both boys and girls growth velocity from the Berkley dataset.

Usage

```
growth_vel
```

Format

growth_vel:

A list with two components:

- **f:** A numeric matrix of shape 69×93 storing a sample of size $N = 93$ of curves evaluated on a grid of size $M = 69$.
- **time:** A numeric vector of size $M = 69$ storing the grid on which the curves **f** have been evaluated.

horizFPCA*Horizontal Functional Principal Component Analysis***Description**

This function calculates vertical functional principal component analysis on aligned data

Usage

```
horizFPCA(warp_data, no = 3, var_exp = NULL, ci = c(-1, 0, 1), showplot = TRUE)
```

Arguments

warp_data	fdawarp object from time_warping of aligned data
no	number of principal components to extract
var_exp	compute no based on value percent variance explained (example: 0.95) will override no
ci	geodesic standard deviations (default = c(-1,0,1))
showplot	show plots of principal directions (default = T)

Value

Returns a hfPCA object containing

gam_pca	warping functions principal directions
psi_pca	srvf principal directions
latent	latent values
U	eigenvectors
vec	shooting vectors
mu	Karcher Mean

References

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
hfPCA <- horizFPCA(simu_warp, no = 3)
```

im	<i>Example Image Data set</i>
----	-------------------------------

Description

Contains two simulated images for registration.

Usage

```
im
```

Format

im:

A list with two components:

- I1: A numeric matrix of shape 64×64 storing the 1st image;
- I2: A numeric matrix of shape 64×64 storing the 2nd image.

invertGamma *Invert Warping Function*

Description

This function calculates the inverse of gamma

Usage

```
invertGamma(gam)
```

Arguments

gam	vector of N samples
-----	-----------------------

Value

Returns gamI inverted vector

References

- Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.
- Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
out <- invertGamma(simu_warp$warping_functions[, 1])
```

inv_exp_map *map square root of warping function to tangent space*

Description

map square root of warping function to tangent space

Usage

```
inv_exp_map(Psi, psi)
```

Arguments

Psi	vector describing psi function at center of tangent space
psi	vector describing psi function to map to tangent space

Value

A numeric array of the same length as the input array `psi` storing the shooting vector of `psi`

jointFPCA

Joint Vertical and Horizontal Functional Principal Component Analysis

Description

This function calculates amplitude and phase joint functional principal component analysis on aligned data

Usage

```
jointFPCA(
  warp_data,
  no = 3,
  var_exp = NULL,
  id = round(length(warp_data$time)/2),
  C = NULL,
  ci = c(-1, 0, 1),
  showplot = T
)
```

Arguments

warp_data	fdawarp object from time_warping of aligned data
no	number of principal components to extract (default = 3)
var_exp	compute no based on value percent variance explained (example: 0.95) will override no
id	integration point for f0 (default = midpoint)
C	balance value (default = NULL)
ci	geodesic standard deviations (default = c(-1,0,1))
showplot	show plots of principal directions (default = T)

Value

Returns a list containing

q_pca	srvf principal directions
f_pca	f principal directions
latent	latent values
coef	coefficients
U	eigenvectors

<code>mu_psi</code>	mean psi function
<code>mu_g</code>	mean g function
<code>id</code>	point use for f(0)
<code>C</code>	optimized phase amplitude ratio

References

- Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.
- Jung, S. L. a. S. (2016). "Combined Analysis of Amplitude and Phase Variations in Functional Data." arXiv:1603.01775.
- Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
jfpca <- jointFPCA(simu_warp, no = 3)
```

`joint_gauss_model` *Gaussian model of functional data using joint Model*

Description

This function models the functional data using a Gaussian model extracted from the principal components of the srvfs using the joint model

Usage

```
joint_gauss_model(warp_data, n = 1, no = 5)
```

Arguments

<code>warp_data</code>	fdawarp object from time_warping of aligned data
<code>n</code>	number of random samples (n = 1)
<code>no</code>	number of principal components (n=4)

Value

Returns a fdawarp object containing

<code>fs</code>	random aligned samples
<code>gams</code>	random warping function samples
<code>ft</code>	random function samples
<code>qs</code>	random srvf samples

References

- Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.
- Jung, S. L. a. S. (2016). "Combined Analysis of Amplitude and Phase Variations in Functional Data." arXiv:1603.01775.

Examples

```
out1 <- joint_gauss_model(simu_warp, n = 10)
```

kmeans_align

K-Means Clustering and Alignment

Description

This function clusters functions and aligns using the elastic square-root velocity function (SRVF) framework.

Usage

```
kmeans_align(
  f,
  time,
  K = 1L,
  seeds = NULL,
  centroid_type = c("mean", "medoid"),
  nonempty = 0L,
  lambda = 0,
  showplot = FALSE,
  smooth_data = FALSE,
  sparam = 25L,
  parallel = FALSE,
  alignment = TRUE,
  rotation = FALSE,
  scale = TRUE,
  omethod = c("DP", "RBFGS"),
  max_iter = 50L,
  thresh = 0.01,
  use_verbose = FALSE
)
```

Arguments

- | | |
|---|---|
| f | Either a numeric matrix or a numeric 3D array specifying the functions that need to be jointly clustered and aligned. <ul style="list-style-type: none"> • If a matrix, it must be of shape $M \times N$. In this case, it is interpreted as a sample of N curves observed on a grid of size M. |
|---|---|

- If a 3D array, it must be of shape $L \times M \times N$ and it is interpreted as a sample of N L -dimensional curves observed on a grid of size M .

time	If this is multidimensional functional data, it is advised that <code>rotation==FALSE</code>
	A numeric vector of length M specifying the grid on which the curves are evaluated.
K	An integer value specifying the number of clusters. Defaults to <code>1L</code> .
seeds	An integer vector of length K specifying the indices of the curves in <code>f</code> which will be chosen as initial centroids. Defaults to <code>NULL</code> in which case such indices are randomly chosen.
centroid_type	A string specifying the type of centroid to compute. Choices are <code>"mean"</code> or <code>"medoid"</code> . Defaults to <code>"mean"</code> .
nonempty	An integer value specifying the minimum number of curves per cluster during the assignment step. Set it to a positive value to avoid the problem of empty clusters. Defaults to <code>0L</code> .
lambda	A numeric value specifying the elasticity. Defaults to <code>0.0</code> .
showplot	A Boolean specifying whether to show plots. Defaults to <code>FALSE</code> .
smooth_data	A Boolean specifying whether to smooth data using a box filter. Defaults to <code>FALSE</code> .
sparam	An integer value specifying the number of box filters applied. Defaults to <code>25L</code> .
parallel	A Boolean specifying whether parallel mode (using <code>foreach::foreach()</code> and the <code>doParallel</code> package) should be activated. Defaults to <code>FALSE</code> .
alignment	A Boolean specifying whether to perform alignment. Defaults to <code>TRUE</code> .
rotation	A Boolean specifying whether to perform rotation. Defaults to <code>to FALSE</code> .
scale	A Boolean specifying whether to scale curves to unit length. Defaults to <code>TRUE</code> .
omethod	A string specifying which method should be used to solve the optimization problem that provides estimated warping functions. Choices are <code>"DP"</code> or <code>"RBFGS"</code> . Defaults to <code>"DP"</code> .
max_iter	An integer value specifying the maximum number of iterations. Defaults to <code>50L</code> .
thresh	A numeric value specifying a threshold on the cost function below which convergence is assumed. Defaults to <code>0.01</code> .
use_verbose	A Boolean specifying whether to display information about the calculations in the console. Defaults to <code>FALSE</code> .

Value

An object of class `fdakma` which is a list containing:

- `f0`: the original functions;
- `q0`: the original SRSFs;
- `fn`: the aligned functions as matrices or a 3D arrays of the same shape than `f0` by clusters in a list;
- `qn`: the aligned SRSFs as matrices or a 3D arrays of the same shape than `f0` separated in clusters in a list;

- **labels**: the cluster memberships as an integer vector;
- **templates**: the centroids in the original functional space;
- **templates.q**: the centroids in SRSF space;
- **distances_to_center**: A numeric vector storing the distances of each observed curve to its center;
- **gam**: the warping functions as matrices or a 3D arrays of the same shape than f_0 by clusters in a list;
- **qun**: cost function value.

References

- Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using Fisher-Rao metric, arXiv:1103.3817v2.
- Tucker, J. D., Wu, W., Srivastava, A., Generative models for functional data using phase and amplitude separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.
- Sangalli, L. M., et al. (2010). "k-mean alignment for curve clustering." Computational Statistics & Data Analysis 54(5): 1219-1233.

Examples

```
## Not run:
out <- kmeans_align(growth_vel$f, growth_vel$time, K = 2)

## End(Not run)
```

LongRunCovMatrix

Long Run Covariance Matrix Estimation for Multivariate Time Series

Description

This function estimates the long run covariance matrix of a given multivariate data sample.

Usage

```
LongRunCovMatrix(mdobj, h = 0, kern_type = "bartlett")
```

Arguments

- | | |
|------------------|---|
| mdobj | A multivariate data object |
| h | The bandwidth parameter. It is strictly non-zero. Choosing the bandwidth parameter to be zero is identical to estimating covariance matrix assuming iid data. |
| kern_type | Kernel function to be used for the estimation of the long run covariance matrix. The choices are c("BT", "PR", "SP", "FT") which are respectively, bartlett, parzen, simple and flat-top kernels. By default the function uses a "bartlett" kernel. |

Value

Returns long run covariance matrix

multiple_align_functions

Group-wise function alignment to specified mean

Description

This function aligns a collection of functions using the elastic square-root slope (srsf) framework.

Usage

```
multiple_align_functions(
  f,
  time,
  mu,
  lambda = 0,
  pen = "roughness",
  showplot = TRUE,
  smooth_data = FALSE,
  sparam = 25,
  parallel = FALSE,
  omethod = "DP",
  MaxItr = 20,
  iter = 2000
)
```

Arguments

<code>f</code>	matrix ($N \times M$) of M functions with N samples
<code>time</code>	vector of size N describing the sample points
<code>mu</code>	vector of size N that <code>f</code> is aligned to
<code>lambda</code>	controls the elasticity (default = 0)
<code>pen</code>	alignment penalty (default="roughness") options are second derivative ("roughness"), geodesic distance from id ("geodesic"), and norm from id ("norm")
<code>showplot</code>	shows plots of functions (default = T)
<code>smooth_data</code>	smooth data using box filter (default = F)
<code>sparam</code>	number of times to apply box filter (default = 25)
<code>parallel</code>	enable parallel mode using <code>foreach()</code> and <code>doParallel</code> package (default=F)
<code>omethod</code>	optimization method (DP,DP2,RBFGS,dBayes,expBayes)
<code>MaxItr</code>	maximum number of iterations
<code>iter</code>	bayesian number of mcmc samples (default 2000)

Value

Returns a fdawarp object containing

<code>f0</code>	original functions
<code>fn</code>	aligned functions - matrix ($N \times M$) of M functions with N samples
<code>qn</code>	aligned SRSFs - similar structure to <code>fn</code>
<code>q0</code>	original SRSF - similar structure to <code>fn</code>
<code>fmean</code>	function mean or median - vector of length N
<code>mqn</code>	SRSF mean or median - vector of length N
<code>gam</code>	warping functions - similar structure to <code>fn</code>
<code>orig.var</code>	Original Variance of Functions
<code>amp.var</code>	Amplitude Variance
<code>phase.var</code>	Phase Variance
<code>qun</code>	Cost Function Value

References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

multivariate_karcher_mean*Karcher Mean of Multivariate Functional Data***Description**

Calculates Karcher mean or median of a collection of multivariate functional data using the elastic square-root velocity (srsvf) framework.

Usage

```
multivariate_karcher_mean(beta, lambda = 0, maxit = 20, ms = "mean")
```

Arguments

<code>beta</code>	$L \times M \times N$ and it is interpreted as a sample of N L -dimensional curves observed on a grid of size M .
<code>lambda</code>	A numeric value specifying the elasticity. Defaults to <code>0.0</code> .
<code>maxit</code>	maximum number of iterations
<code>ms</code>	string defining whether the Karcher mean ("mean") or Karcher median ("median") is returned (default = "mean")

Value

Returns a list containing

<code>mu</code>	mean srvf
<code>betamean</code>	mean or median curve
<code>type</code>	string indicating whether mean or median is returned
<code>betan</code>	aligned curves
<code>q</code>	array of srvfs
<code>qn</code>	array of aligned srvfs
<code>gam</code>	array of warping functions
<code>E</code>	energy
<code>qun</code>	cost function

References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 33 (7), 1415-1428.

Examples

```
out <- multivariate_karcher_mean(beta[, , 1, 1:2], maxit = 2)
# note: use more functions, small for speed
```

`optimum.reparam`

Align two functions

Description

This function aligns the SRVF^s of two functions in R^1 defined on an interval $[t_{\min}, t_{\max}]$ using dynamic programming or RBFGS

Usage

```
optimum.reparam(
  Q1,
  T1,
  Q2,
  T2,
  lambda = 0,
  pen = "roughness",
  method = c("DP", "DPo", "SIMUL", "RBFGS"),
  f1o = 0,
  f2o = 0,
  nbhd_dim = 7
)
```

Arguments

Q1	A numeric matrix of shape n_points x n_dimensions specifying the SRSF of the 1st n_dimensions-dimensional function evaluated on a grid of size n_points of its univariate domain.
T1	A numeric vector of size n_points specifying the grid on which the 1st SRSF is evaluated.
Q2	A numeric matrix of shape n_points x n_dimensions specifying the SRSF of the 2nd n_dimensions-dimensional function evaluated on a grid of size n_points of its univariate domain.
T2	A numeric vector of size n_points specifying the grid on which the 1st SRSF is evaluated.
lambda	A numeric value specifying the amount of warping. Defaults to 0.0.
pen	alignment penalty (default="roughness") options are second derivative ("roughness"), geodesic distance from id ("geodesic"), and norm from id ("l2gam"), srvf norm from id ("l2psi")
method	A string specifying the optimization method. Choices are "DP", "DPo", "SIMUL", or "RBFGS". Defaults to "DP".
f1o	A numeric vector of size n_dimensions specifying the value of the 1st function at $t = t_{\min}$. Defaults to rep(0, n_dimensions).
f2o	A numeric vector of size n_dimensions specifying the value of the 2nd function at $t = t_{\min}$. Defaults to rep(0, n_dimensions).
nbhd_dim	size of the grid (default = 7)

Value

A numeric vector of size n_points storing discrete evaluations of the estimated boundary-preserving warping diffeomorphism on the initial grid.

References

- Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using Fisher-Rao metric, arXiv:1103.3817v2.
- Tucker, J. D., Wu, W., Srivastava, A., Generative models for functional data using phase and amplitude separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
q <- f_to_srvf(simu_data$f, simu_data$time)
gam <- optimum.reparam(q[, 1], simu_data$time, q[, 2], simu_data$time)
```

outlier.detection *Outlier Detection*

Description

This function calculates outlier's using geodesic distances of the SRVF's from the median

Usage

```
outlier.detection(q, time, mq, k = 1.5)
```

Arguments

<code>q</code>	matrix ($N \times M$) of M SRVF functions with N samples
<code>time</code>	vector of size N describing the sample points
<code>mq</code>	median calculated using <code>time_warping()</code>
<code>k</code>	cutoff threshold (default = 1.5)

Value

<code>q_outlier</code>	outlier functions
------------------------	-------------------

References

- Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.
- Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
q_outlier <- outlier.detection(
  q = toy_warp$q0,
  time = toy_data$time,
  mq = toy_warp$mqn,
  k = .1
)
```

`pair_align_functions` *Align two functions*

Description

This function aligns two functions using SRSF framework. It will align f2 to f1

Usage

```
pair_align_functions(
  f1,
  f2,
  time,
  lambda = 0,
  pen = "roughness",
  method = "DP",
  w = 0.01,
  iter = 2000
)
```

Arguments

<code>f1</code>	function 1
<code>f2</code>	function 2
<code>time</code>	sample points of functions
<code>lambda</code>	controls amount of warping (default = 0)
<code>pen</code>	alignment penalty (default="roughness") options are second derivative ("roughness"), geodesic distance from id ("geodesic"), and norm from id ("norm")
<code>method</code>	controls which optimization method (default="DP") options are Dynamic Programming ("DP"), Coordinate Descent ("DP2"), Riemannian BFGS ("RBFGS"), Simultaneous Alignment ("SIMUL"), Dirichlet Bayesian ("dBayes"), and Expomap Bayesian ("expBayes")
<code>w</code>	controls LRBFGS (default = 0.01)
<code>iter</code>	number of mcmc iterations for mcmc method (default 2000)

Value

Returns a list containing

<code>f2tilde</code>	aligned f2
<code>gam</code>	warping function

References

- Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.
- Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.
- Cheng, W., Dryden, I. L., and Huang, X. (2016). Bayesian registration of functions and curves. Bayesian Analysis, 11(2), 447-475.
- Lu, Y., Herbei, R., and Kurtek, S. (2017). Bayesian registration of functions with a Gaussian process prior. Journal of Computational and Graphical Statistics, DOI: 10.1080/10618600.2017.1336444.

Examples

```
out <- pair_align_functions(
  f1 = simu_data$f[, 1],
  f2 = simu_data$f[, 2],
  time = simu_data$time
)
```

pair_align_functions_bayes
Align two functions

Description

This function aligns two functions using Bayesian SRSF framework. It will align f2 to f1

Usage

```
pair_align_functions_bayes(
  f1,
  f2,
  timet,
  iter = 15000,
  times = 5,
  tau = ceiling(times * 0.4),
  powera = 1,
  showplot = TRUE,
  extrainfo = FALSE
)
```

Arguments

f1	function 1
f2	function 2
timet	sample points of functions

iter	number of iterations (default = 15000)
times	factor of length of subsample points to look at (default = 5)
tau	standard deviation of Normal prior for increment (default ceil(times*.4))
powera	Dirichlet prior parameter (default 1)
showplot	shows plots of functions (default = T)
extrainfo	T/F whether additional information is returned

Value

Returns a list containing

f1	function 1
f2_q	registered function using quotient space
gam_q	warping function quotient space
f2_a	registered function using ambient space
q2_a	warping function ambient space
match_collect	posterior samples from warping function (returned if extrainfo=TRUE)
dist_collect	posterior samples from the distances (returned if extrainfo=TRUE)
kappa_collect	posterior samples from kappa (returned if extrainfo=TRUE)
log_collect	log-likelihood of each sample (returned if extrainfo=TRUE)
pct_accept	vector of acceptance ratios for the warping function (returned if extrainfo=TRUE)

References

Cheng, W., Dryden, I. L., and Huang, X. (2016). Bayesian registration of functions and curves. *Bayesian Analysis*, 11(2), 447-475.

Examples

```
out <- pair_align_functions_bayes(
  f1 = simu_data$f[, 1],
  f2 = simu_data$f[, 2],
  timet = simu_data$time
)
```

pair_align_functions_expmmap*Align two functions using geometric properties of warping functions*

Description

This function aligns two functions using Bayesian framework. It will align f2 to f1. It is based on mapping warping functions to a hypersphere, and a subsequent exponential mapping to a tangent space. In the tangent space, the Z-mixture pCN algorithm is used to explore both local and global structure in the posterior distribution.

Usage

```
pair_align_functions_expmmap(
  f1,
  f2,
  timet,
  iter = 20000,
  burnin = min(5000, iter/2),
  alpha0 = 0.1,
  beta0 = 0.1,
  zpcn = list(betas = c(0.5, 0.05, 0.005, 1e-04), probs = c(0.1, 0.1, 0.7, 0.1)),
  propvar = 1,
  init.coef = rep(0, 2 * 10),
  npoints = 200,
  extrainfo = FALSE
)
```

Arguments

f1	observed data, numeric vector
f2	observed data, numeric vector
timet	sample points of functions
iter	length of the chain
burnin	number of burnin MCMC iterations
alpha0, beta0	IG parameters for the prior of sigma1
zpcn	list of mixture coefficients and prior probabilities for Z-mixture pCN algorithm of the form list(betas, probs), where betas and probs are numeric vectors of equal length
propvar	variance of proposal distribution
init.coef	initial coefficients of warping function in exponential map; length must be even
npoints	number of sample points to use during alignment
extrainfo	T/F whether additional information is returned

Details

The Z-mixture pCN algorithm uses a mixture distribution for the proposal distribution, controlled by input parameter zpcn. The zpcn\$betas must be between 0 and 1, and are the coefficients of the mixture components, with larger coefficients corresponding to larger shifts in parameter space. The zpcn\$probs give the probability of each shift size.

Value

Returns a list containing

f2_warped	f2 aligned to f1
gamma	Posterior mean gamma function
g.coef	matrix with iter columns, posterior draws of g.coef
psi	Posterior mean psi function
sigma1	numeric vector of length iter, posterior draws of sigma1
accept	Boolean acceptance for each sample (if extrainfo=TRUE)
betas.ind	Index of zpcn mixture component for each sample (if extrainfo=TRUE)
logl	numeric vector of length iter, posterior loglikelihood (if extrainfo=TRUE)
gamma_mat	Matrix of all posterior draws of gamma (if extrainfo=TRUE)
gamma_q025	Lower 0.025 quantile of gamma (if extrainfo=TRUE)
gamma_q975	Upper 0.975 quantile of gamma (if extrainfo=TRUE)
sigma_eff_size	Effective sample size of sigma (if extrainfo=TRUE)
psi_eff_size	Vector of effective sample sizes of psi (if extrainfo=TRUE)
xdist	Vector of posterior draws from xdist between registered functions (if extrainfo=TRUE)
ydist	Vector of posterior draws from ydist between registered functions (if extrainfo=TRUE)

References

Lu, Y., Herbei, R., and Kurtek, S. (2017). Bayesian registration of functions with a Gaussian process prior. Journal of Computational and Graphical Statistics, DOI: 10.1080/10618600.2017.1336444.

Examples

```
## Not run:
# This is an MCMC algorithm and takes a long time to run
myzpcn <- list(
  betas = c(0.1, 0.01, 0.005, 0.0001),
  probs = c(0.2, 0.2, 0.4, 0.2)
)
out <- pair_align_functions_expomap(
  f1 = simu_data$f[, 1],
  f2 = simu_data$f[, 2],
  timet = simu_data$time,
  zpcn = myzpcn,
  extrainfo = TRUE
)
```

```

# overall acceptance ratio
mean(out$accept)
# acceptance ratio by zpcn coefficient
with(out, tapply(accept, myzpcn$betas[betas.ind], mean))

## End(Not run)

```

pair_align_image

Pairwise align two images This function aligns to images using the q-map framework

Description

Pairwise align two images This function aligns to images using the q-map framework

Usage

```

pair_align_image(
  I1,
  I2,
  M = 5,
  ortho = TRUE,
  basis_type = "t",
  resizei = FALSE,
  N = 64,
  stepsize = 1e-05,
  itermax = 1000
)

```

Arguments

I1	reference image
I2	image to warp
M	number of basis elements (default=5)
ortho	orthonormalize basis (default=TRUE)
basis_type	("t","s","i","o"; default="t")
resizei	resize image (default=TRUE)
N	size of resized image (default=64)
stepsize	gradient stepsize (default=1e-5)
itermax	maximum number of iterations (default=1000)

Value

Returns a list containing

Inew	aligned I2
gam	warping function

References

Q. Xie, S. Kurtek, E. Klassen, G. E. Christensen and A. Srivastava. Metric-based pairwise and multiple image registration. IEEE European Conference on Computer Vision (ECCV), September, 2014

Examples

```
## Not run:
# This is a gradient descent algorithm and takes a long time to run
out <- pair_align_image(im$I1, im$I2)

## End(Not run)
```

pcaTB

Tolerance Bound Calculation using Elastic Functional PCA

Description

This function computes tolerance bounds for functional data containing phase and amplitude variation using principal component analysis

Usage

```
pcaTB(f, time, m = 4, B = 1e+05, a = 0.05, p = 0.99)
```

Arguments

f	matrix of functions
time	vector describing time sampling
m	number of principal components (default = 4)
B	number of monte carlo iterations
a	confidence level of tolerance bound (default = 0.05)
p	coverage level of tolerance bound (default = 0.99)

Value

Returns a list containing

pca	pca output
tol	tolerance factor

References

- J. D. Tucker, J. R. Lewis, C. King, and S. Kurtek, “A Geometric Approach for Computing Tolerance Bounds for Elastic Functional Data,” Journal of Applied Statistics, 10.1080/02664763.2019.1645818, 2019.
- Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.
- Jung, S. L. a. S. (2016). "Combined Analysis of Amplitude and Phase Variations in Functional Data." arXiv:1603.01775.

Examples

```
## Not run:
out1 <- pcaTB(simu_data$f, simu_data$time)

## End(Not run)
```

predict.hfPCA

Elastic Prediction for functional PCA

Description

This function performs projection of new functions on fPCA basis

Usage

```
## S3 method for class 'hfPCA'
predict(object, newdata = NULL, ...)
```

Arguments

- | | |
|---------|---|
| object | Object of class inheriting from "horizFPCA" |
| newdata | An optional matrix in which to look for functions with which to predict. If omitted, the original functions are used. |
| ... | additional arguments affecting the predictions produced |

Value

- Returns a matrix
- | | |
|---|------------------------|
| a | principle coefficients |
|---|------------------------|

References

- Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

predict.jfpca	<i>Elastic Prediction for functional PCA</i>
---------------	--

Description

This function performs projection of new functions on fPCA basis

Usage

```
## S3 method for class 'jfpca'  
predict(object, newdata = NULL, ...)
```

Arguments

object	Object of class inheriting from "jointFPCA"
newdata	An optional matrix in which to look for functions with which to predict. If omitted, the original functions are used.
...	additional arguments affecting the predictions produced

Value

Returns a matrix

a principle coefficients

References

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

predict.lpcr	<i>Elastic Prediction for functional logistic PCR Model</i>
--------------	---

Description

This function performs prediction from an elastic logistic fPCR regression model with phase-variability

Usage

```
## S3 method for class 'lpcr'  
predict(object, newdata = NULL, y = NULL, ...)
```

Arguments

object	Object of class inheriting from "elastic.pcr.regression"
newdata	An optional matrix in which to look for variables with which to predict. If omitted, the fitted values are used.
y	An optional vector of labels to calculate PC. If omitted, PC is NULL
...	additional arguments affecting the predictions produced

Value

Returns a list containing

y_pred	predicted probabilities of the class of newdata
y_labels	class labels of newdata
PC	probability of classification

References

J. D. Tucker, J. R. Lewis, and A. Srivastava, “Elastic Functional Principal Component Regression,” Statistical Analysis and Data Mining, 10.1002/sam.11399, 2018.

Description

This function performs prediction from an elastic multinomial logistic fPCR regression model with phase-variability

Usage

```
## S3 method for class 'mlpcr'
predict(object, newdata = NULL, y = NULL, ...)
```

Arguments

object	Object of class inheriting from "elastic.pcr.regression"
newdata	An optional matrix in which to look for variables with which to predict. If omitted, the fitted values are used.
y	An optional vector of labels to calculate PC. If omitted, PC is NULL
...	additional arguments affecting the predictions produced

Value

Returns a list containing

y_pred	predicted probabilities of the class of newdata
y_labels	class labels of newdata
PC	probability of classification per class
PC.comb	total probability of classification

References

J. D. Tucker, J. R. Lewis, and A. Srivastava, “Elastic Functional Principal Component Regression,” Statistical Analysis and Data Mining, 10.1002/sam.11399, 2018.

predict.pcr

Elastic Prediction for functional PCR Model

Description

This function performs prediction from an elastic pcr regression model with phase-variability

Usage

```
## S3 method for class 'pcr'  
predict(object, newdata = NULL, y = NULL, ...)
```

Arguments

object	Object of class inheriting from "elastic.pcr.regression"
newdata	An optional matrix in which to look for variables with which to predict. If omitted, the fitted values are used.
y	An optional vector of responses to calculate SSE. If omitted, SSE is NULL
...	additional arguments affecting the predictions produced

Value

Returns a list containing

y_pred	predicted values of newdata
SSE	sum of squared errors

References

J. D. Tucker, J. R. Lewis, and A. Srivastava, “Elastic Functional Principal Component Regression,” Statistical Analysis and Data Mining, 10.1002/sam.11399, 2018.

predict.vfpca

*Elastic Prediction for functional PCA***Description**

This function performs projection of new functions on fPCA basis

Usage

```
## S3 method for class 'vfpca'
predict(object, newdata = NULL, ...)
```

Arguments

- | | |
|---------|---|
| object | Object of class inheriting from "vertFPCA" |
| newdata | An optional matrix in which to look for functions with which to predict. If omitted, the original functions are used. |
| ... | additional arguments affecting the predictions produced |

Value

- Returns a matrix
- | | |
|---|------------------------|
| a | principle coefficients |
|---|------------------------|

References

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

q_to_curve

*Convert to curve space***Description**

This function converts SRVF to curves

Usage

```
q_to_curve(q, scale = 1)
```

Arguments

- | | |
|-------|--|
| q | either a matrix of shape $n \times T$ describing SRVF or SRVF of multidimensional functional data in R^n , where n is the dimension and T is the number of time points |
| scale | scale of original beta (default = 1) |

Value

beta array describing curve

References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

Examples

```
q <- curve_to_q(beta[, , 1, 1])$q
beta1 <- q_to_curve(q)
```

reparam_curve

Align two curves

Description

This function aligns two SRVF functions using Dynamic Programming. If the curves beta1 and beta2 are describing multidimensional functional data, then rotation == FALSE and mode == '0'

Usage

```
reparam_curve(
  beta1,
  beta2,
  lambda = 0,
  method = "DP",
  w = 0.01,
  rotated = TRUE,
  isclosed = FALSE,
  mode = "0"
)
```

Arguments

beta1	curve 1, provided as a matrix of dimensions $n \times M$ for n -dimensional curve evaluated on M sample points
beta2	curve 1, provided as a matrix of dimensions $n \times M$ for n -dimensional curve evaluated on M sample points
lambda	controls amount of warping (default = 0)
method	controls which optimization method. Options are Dynamic Programming ("DP"). (default = "DP")
w	controls LRBFGS (default = 0.01)
rotated	boolean if rotation is desired
isclosed	boolean if curve is closed
mode	Open ("0") or Closed ("C") curves

Value

return a List containing

gam	warping function
R	rotation matrix
tau	seed point

References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 33 (7), 1415-1428.

Examples

```
gam <- reparam_curve(beta[, , 1, 1], beta[, , 1, 5])$gam
```

reparam_image

Find optimum reparameterization between two images

Description

Finds the optimal warping function between two images using the elastic framework

Usage

```
reparam_image(It, Im, gam, b, stepsize = 1e-05, itermax = 1000, lmark = FALSE)
```

Arguments

It	template image matrix
Im	test image matrix
gam	initial warping array
b	basis matrix
stepsize	gradient stepsize (default=1e-5)
itermax	maximum number of iterations (default=1000)
lmark	use landmarks (default=FALSE)

Value

Returns a list containing

gamnew	final warping
Inew	aligned image
H	energy
stepsize	final stepsize

References

Q. Xie, S. Kurtek, E. Klassen, G. E. Christensen and A. Srivastava. Metric-based pairwise and multiple image registration. IEEE European Conference on Computer Vision (ECCV), September, 2014

resamplecurve

Resample Curve

Description

This function resamples a curve to a number of points

Usage

```
resamplecurve(x, N = 100, mode = "O")
```

Arguments

x	matrix defining curve (n,T)
N	Number of samples to re-sample curve, N usually is > T
mode	Open ("O") or Closed ("C") curves

Value

xn matrix defining resampled curve

References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

Examples

```
xn <- resamplecurve(beta[, , 1], 200)
```

`rgam`*Random Warping***Description**

Generates random warping functions

Usage

```
rgam(N, sigma, num)
```

Arguments

<code>N</code>	length of warping function
<code>sigma</code>	variance of warping functions
<code>num</code>	number of warping functions

Value

gam warping functions

References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
gam = rgam(N=101, sigma=.01, num=35)
```

`sample_shapes`*Sample shapes from model***Description**

Sample shapes from model

Usage

```
sample_shapes(mu, K, mode = "0", no = 3, numSamp = 10)
```

Arguments

mu	array (n,T) of mean srvf
K	array (2T,2T) covariance matrix
mode	Open ("O") or Closed ("C") curves
no	number of principal components
numSamp	number of samples

Value

samples list of sample curves

References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

Examples

```
out <- curve_karcher_mean(beta[, , 1, 1:2], maxit = 2)
# note: use more shapes, small for speed
K <- curve_karcher_cov(out$v)
samples <- sample_shapes(out$mu, K)
```

simu_data

Simulated two Gaussian Dataset

Description

A functional dataset where the individual functions are given by: $y_i(t) = z_{i,1}e^{-(t-1.5)^2/2} + z_{i,2}e^{-(t+1.5)^2/2}$, $t \in [-3, 3]$, $i = 1, 2, \dots, 21$, where $z_{i,1}$ and $z_{i,2}$ are *i.i.d.* normal with mean one and standard deviation 0.25. Each of these functions is then warped according to: $\gamma_i(t) = 6\left(\frac{e^{a_i(t+3)/6}-1}{e^{a_i}-1}\right) - 3$ if $a_i \neq 0$, otherwise $\gamma_i = \gamma_{id}$ ($\text{gamma}_{id}(t) = t$) is the identity warping). The variables are as follows: f containing the 21 functions of 101 samples and time which describes the sampling.

Usage

simu_data

Format**simu_data:**

A list with 2 components:

- **f**: A numeric matrix of shape 101×21 storing a sample of size $N = 21$ of curves evaluated on a grid of size $M = 101$.
- **time**: A numeric vector of size $M = 101$ storing the grid on which the curves **f** have been evaluated.

simu_warp

*Aligned Simulated two Gaussian Dataset***Description**

A functional dataset where the individual functions are given by: $y_i(t) = z_{i,1}e^{-(t-1.5)^2/2} + z_{i,2}e^{-(t+1.5)^2/2}$, $t \in [-3, 3]$, $i = 1, 2, \dots, 21$, where $z_{i,1}$ and $z_{i,2}$ are *i.i.d.* normal with mean one and standard deviation 0.25. Each of these functions is then warped according to: $\gamma_i(t) = 6\left(\frac{e^{a_i(t+3)/6}-1}{e^{a_i}-1}\right) - 3$ if $a_i \neq 0$, otherwise $\gamma_i = \gamma_{id}$ ($\text{gamma}_{id}(t) = t$) is the identity warping). The variables are as follows: **f** containing the 21 functions of 101 samples and time which describes the sampling which has been aligned.

Usage

simu_warp

Format**simu_warp:**A list which contains the output of the [time_warping\(\)](#) function applied on the data set **simu_data**.

simu_warp_median

*Aligned Simulated two Gaussian Dataset using Median***Description**

A functional dataset where the individual functions are given by: $y_i(t) = z_{i,1}e^{-(t-1.5)^2/2} + z_{i,2}e^{-(t+1.5)^2/2}$, $t \in [-3, 3]$, $i = 1, 2, \dots, 21$, where $z_{i,1}$ and $z_{i,2}$ are *i.i.d.* normal with mean one and standard deviation 0.25. Each of these functions is then warped according to: $\gamma_i(t) = 6\left(\frac{e^{a_i(t+3)/6}-1}{e^{a_i}-1}\right) - 3$ if $a_i \neq 0$, otherwise $\gamma_i = \gamma_{id}$ ($\text{gamma}_{id}(t) = t$) is the identity warping). The variables are as follows: **f** containing the 21 functions of 101 samples and time which describes the sampling which has been aligned.

Usage

simu_warp_median

Format

`simu_warp_median:`

A list which contains the output of the `time_warping()` function finding the median applied on the data set `simu_data`.

`smooth.data`

Smooth Functions

Description

This function smooths functions using standard box filter

Usage

```
smooth.data(f, sparam)
```

Arguments

<code>f</code>	matrix ($N \times M$) of M functions with N samples
<code>sparam</code>	number of times to run box filter

Value

fo smoothed functions

References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
fo <- smooth.data(simu_data$f, 25)
```

SqrtMean*SRVF transform of warping functions***Description**

This function calculates the srvf of warping functions with corresponding shooting vectors and finds the mean

Usage

```
SqrtMean(gam)
```

Arguments

gam	matrix ($N \times M$) of M warping functions with N samples
-----	---

Value

Returns a list containing

mu	Karcher mean psi function
gam_mu	Karcher mean warping function
psi	srvf of warping functions
vec	shooting vectors

References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
out <- SqrtMean(simu_warp$warping_functions)
```

<code>SqrtMeanInverse</code>	<i>SRVF transform of warping functions</i>
------------------------------	--

Description

This function calculates the srvf of warping functions with corresponding shooting vectors and finds the inverse of mean

Usage

```
SqrtMeanInverse(gam)
```

Arguments

<code>gam</code>	matrix ($N \times M$) of M warping functions with N samples
------------------	---

Value

`gamI` inverse of Karcher mean warping function

References

- Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.
- Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
gamI <- SqrtMeanInverse(simu_warp$warping_functions)
```

<code>SqrtMedian</code>	<i>SRVF transform of warping functions</i>
-------------------------	--

Description

This function calculates the srvf of warping functions with corresponding shooting vectors and finds the median

Usage

```
SqrtMedian(gam)
```

Arguments

<code>gam</code>	matrix ($N \times M$) of M warping functions with N samples
------------------	---

Value

Returns a list containing

median	Karcher median psi function
gam_median	Karcher mean warping function
psi	srvf of warping functions
vec	shooting vectors

References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
out <- SqrtMedian(simu_warp_median$warping_functions)
```

srvf_to_f*Transformation from SRSF Space***Description**

This function transforms SRVFs back to the original functional space for functions in R^1 .

Usage

```
srvf_to_f(q, time, f0 = 0)
```

Arguments

q	Either a numeric vector of a numeric matrix or a numeric array specifying the SRSFs that need to be transformed. <ul style="list-style-type: none"> If a vector, it must be of shape M and it is interpreted as a single 1-dimensional curve observed on a grid of size M. If a matrix, it must be of shape $M \times N$. In this case, it is interpreted as a sample of N curves observed on a grid of size M, unless $M = 1$ in which case it is interpreted as a single 1-dimensional curve observed on a grid of size M.
time	A numeric vector of length M specifying the grid on which SRSFs are evaluated.
f0	Either a numeric value or a numeric vector of or a numeric matrix specifying the initial value of the curves in the original functional space. It must be: <ul style="list-style-type: none"> a value if q represents a single SRSF. a vector of length N if q represents a sample of N SRVFs

Value

A numeric array of the same shape as the input q storing the transformation of the SRVF_s q back to the original functional space.

References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative models for functional data using amplitude and phase separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
q <- f_to_srvf(simu_data$f, simu_data$time)
f <- srvf_to_f(q, simu_data$time, simu_data$f[1, ])
```

time_warping

*Alignment of univariate functional data***Description**

This function aligns a collection of 1-dimensional curves that are observed on the same grid.

Usage

```
time_warping(
  f,
  time,
  lambda = 0,
  penalty_method = c("roughness", "geodesic", "norm"),
  centroid_type = c("mean", "median"),
  center_warpings = TRUE,
  smooth_data = FALSE,
  sparam = 25L,
  parallel = FALSE,
  optim_method = c("DP", "DPo", "DP2", "RBFGS"),
  max_iter = 20L
)
```

Arguments

- | | |
|--------|---|
| f | A numeric matrix of shape $M \times N$ specifying a sample of N curves observed on a grid of size M . |
| time | A numeric vector of length M specifying the common grid on which all curves f have been observed. |
| lambda | A numeric value specifying the elasticity. Defaults to 0.0. |

penalty_method	A string specifying the penalty term used in the formulation of the cost function to minimize for alignment. Choices are "roughness" which uses the norm of the second derivative, "geodesic" which uses the geodesic distance to the identity and "norm" which uses the Euclidean distance to the identity. Defaults to "roughness".
centroid_type	A string specifying the type of centroid to align to. Choices are "mean" or "median". Defaults to "mean".
center_warpings	A boolean specifying whether to center the estimated warping functions. Defaults to TRUE.
smooth_data	A boolean specifying whether to smooth curves using a box filter. Defaults to FALSE.
sparam	An integer value specifying the number of times to apply the box filter. Defaults to 25L. This is used only when smooth_data = TRUE.
parallel	A boolean specifying whether to run calculations in parallel. Defaults to FALSE.
optim_method	A string specifying the algorithm used for optimization. Choices are "DP", "DPO", and "RBFGS". Defaults to "DP".
max_iter	An integer value specifying the maximum number of iterations. Defaults to 20L.

Value

An object of class `fdawarp` which is a list with the following components:

- `time`: a numeric vector of length M storing the original grid;
- `f0`: a numeric matrix of shape $M \times N$ storing the original sample of N functions observed on a grid of size M ;
- `q0`: a numeric matrix of the same shape as `f0` storing the original SRSFs;
- `fn`: a numeric matrix of the same shape as `f0` storing the aligned functions;
- `qn`: a numeric matrix of the same shape as `f0` storing the aligned SRSFs;
- `fmean`: a numeric vector of length M storing the mean or median curve;
- `mqn`: a numeric vector of length M storing the mean or median SRSF;
- `warping_functions`: a numeric matrix of the same shape as `f0` storing the estimated warping functions;
- `original_variance`: a numeric value storing the variance of the original sample;
- `amplitude_variance`: a numeric value storing the variance in amplitude of the aligned sample;
- `phase_variance`: a numeric value storing the variance in phase of the aligned sample;
- `qun`: a numeric vector of maximum length `max_iter` + 2 storing the values of the cost function after each iteration;
- `lambda`: the input parameter `lambda` which specifies the elasticity;
- `centroid_type`: the input centroid type;
- `optim_method`: the input optimization method;
- `inverse_average_warping_function`: the inverse of the mean estimated warping function;
- `rsamps`: TO DO.

References

- Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using Fisher-Rao metric, arXiv:1103.3817v2.
- Tucker, J. D., Wu, W., Srivastava, A., Generative models for functional data using phase and amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
## Not run:  
out <- time_warping(simu_data$f, simu_data$time)  
  
## End(Not run)
```

toy_data

Distributed Gaussian Peak Dataset

Description

A functional dataset where the individual functions are given by a Gaussian peak with locations along the x -axis. The variables are as follows: f containing the 29 functions of 101 samples and $time$ which describes the sampling.

Usage

toy_data

Format

toy_data:

A list with two components:

- f : A numeric matrix of shape 101×29 storing a sample of size $N = 29$ of curves evaluated on a grid of size $M = 101$.
- $time$: A numeric vector of size $M = 101$ storing the grid on which the curves f have been evaluated.

toy_warp

*Aligned Distributed Gaussian Peak Dataset***Description**

A functional dataset where the individual functions are given by a Gaussian peak with locations along the x -axis. The variables are as follows: f containing the 29 functions of 101 samples and $time$ which describes the sampling which has been aligned.

Usage

toy_warp

Format**toy_warp:**

A list which contains the output of the [time_warping\(\)](#) function applied on the data set toy_data.

vertFPCA

*Vertical Functional Principal Component Analysis***Description**

This function calculates vertical functional principal component analysis on aligned data

Usage

```
vertFPCA(
  warp_data,
  no = 3,
  var_exp = NULL,
  id = round(length(warp_data$time)/2),
  ci = c(-1, 0, 1),
  showplot = TRUE
)
```

Arguments

warp_data	fdawarp object from time_warping of aligned data
no	number of principal components to extract
var_exp	compute no based on value percent variance explained (example: 0.95) will override no
id	point to use for $f(0)$ (default = midpoint)
ci	geodesic standard deviations (default = c(-1,0,1))
showplot	show plots of principal directions (default = T)

Value

Returns a vfPCA object containing

q_pca	srvf principal directions
f_pca	f principal directions
latent	latent values
coef	coefficients
U	eigenvectors
id	point used for f(0)

References

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
vfPCA <- vertFPCA(simu_warp, no = 3)
```

v_to_gam

map shooting vector to warping function at identity

Description

map shooting vector to warping function at identity

Usage

```
v_to_gam(v)
```

Arguments

v	Either a numeric vector or a numeric matrix or a numeric array specifying the shooting vectors
---	--

Value

A numeric array of the same shape as the input array v storing the shooting vectors of v obtained via finite differences.

warp_f_gamma*Warp Function***Description**

This function warps function f by γ

Usage

```
warp_f_gamma(f, time, gamma, spl.int = FALSE)
```

Arguments

<i>f</i>	vector function
<i>time</i>	time
<i>gamma</i>	vector warping function
<i>spl.int</i>	use spline interpolation (default F)

Value

fnew warped function

References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
fnew <- warp_f_gamma(
  f = simu_data$f[, 1],
  time = simu_data$time,
  gamma = seq(0, 1, length.out = 101)
)
```

warp_q_gamma

Warp SRSF

Description

This function warps srsf q by γ

Usage

```
warp_q_gamma(q, time, gamma, spl.int = FALSE)
```

Arguments

q	vector
time	time
gamma	vector warping function
spl.int	use spline interpolation (default F)

Value

qnew warped function

References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Examples

```
q <- f_to_srvf(simu_data$f, simu_data$time)
qnew <- warp_q_gamma(q[, 1], simu_data$time, seq(0, 1, length.out = 101))
```

Index

- * **alignment**
 - curve_geodesic, 10
 - curve_karcher_cov, 11
 - curve_karcher_mean, 11
 - curve_pair_align, 13
 - curve_principal_directions, 14
 - curve_srvf_align, 15
 - curve_to_q, 16
 - elastic.logistic, 19
 - elastic.lpcr.regression, 20
 - elastic.mlogistic, 21
 - elastic.mlpcr.regression, 22
 - elastic.pcr.regression, 24
 - elastic.prediction, 25
 - elastic.regression, 26
 - elastic_amp_change_ff, 27
 - elastic_change_fPCA, 28
 - elastic_ph_change_ff, 30
 - f_to_srvf, 35
 - gam_to_v, 36
 - gradient, 37
 - horizFPCA, 38
 - inv_exp_map, 40
 - invertGamma, 40
 - jointFPCA, 41
 - kmeans_align, 43
 - multiple_align_functions, 46
 - multivariate_karcher_mean, 47
 - optimum.reparam, 48
 - pair_align_functions, 51
 - pair_align_image, 56
 - predict.hfpca, 58
 - predict.jfpca, 59
 - predict.lpcr, 59
 - predict.mlpcr, 60
 - predict.pcr, 61
 - predict.vfpca, 62
 - q_to_curve, 62
 - reparam_curve, 63
- reparam_image, 64
- resamplecurve, 65
- sample_shapes, 66
- smooth.data, 69
- SqrtMean, 70
- SqrtMeanInverse, 71
- SqrtMedian, 71
- srvf_to_f, 72
- time_warping, 73
- v_to_gam, 77
- vertFPCA, 76
- warp_f_gamma, 78
- warp_q_gamma, 79
- * **bayesian**
 - function_group_warp_bayes, 32
 - function_mean_bayes, 34
 - pair_align_functions_bayes, 52
- * **bootstrap**
 - bootTB, 6
- * **bounds**
 - bootTB, 6
- * **changepoint**
 - elastic_amp_change_ff, 27
 - elastic_change_fPCA, 28
 - elastic_ph_change_ff, 30
- * **clustering**
 - kmeans_align, 43
- * **datasets**
 - beta, 5
 - growth_vel, 38
 - im, 39
 - simu_data, 67
 - simu_warp, 68
 - simu_warp_median, 68
 - toy_data, 75
 - toy_warp, 76
- * **depth**
 - curve_depth, 9
 - elastic.depth, 17

- * **detection**
 - outlier.detection, 50
- * **diffeomorphism**
 - rgam, 66
- * **distances**
 - calc_shape_dist, 8
 - elastic.distance, 18
- * **function**
 - rgam, 66
- * **image**
 - pair_align_image, 56
 - reparam_image, 64
- * **outlier**
 - outlier.detection, 50
- * **pca tolerance bounds**
 - pcaTB, 57
- * **pca**
 - align_fPCA, 3
 - gauss_model, 36
 - joint_gauss_model, 42
- * **regression**
 - elastic.logistic, 19
 - elastic.lpcr.regression, 20
 - elastic.mlogistic, 21
 - elastic.mlpcr.regression, 22
 - elastic.pcr.regression, 24
 - elastic.prediction, 25
 - elastic.regression, 26
 - predict.hfPCA, 58
 - predict.jfPCA, 59
 - predict.lpcr, 59
 - predict.mlpcr, 60
 - predict.pcr, 61
 - predict.vfPCA, 62
- * **srsf alignment**
 - function_group_warp_bayes, 32
 - function_mean_bayes, 34
 - pair_align_functions_bayes, 52
- * **srsf**
 - kmeans_align, 43
 - multiple_align_functions, 46
 - pair_align_functions, 51
 - time_warping, 73
- * **srvf alignment**
 - align_fPCA, 3
 - curve_depth, 9
 - elastic.depth, 17
 - elastic.distance, 18
- * **srvf**
 - curve_geodesic, 10
 - curve_karcher_cov, 11
 - curve_karcher_mean, 11
 - curve_pair_align, 13
 - curve_principal_directions, 14
 - curve_srvf_align, 15
 - curve_to_q, 16
 - elastic.logistic, 19
 - elastic.lpcr.regression, 20
 - elastic.mlogistic, 21
 - elastic.mlpcr.regression, 22
 - elastic.pcr.regression, 24
 - elastic.prediction, 25
 - elastic.regression, 26
 - elastic_amp_change_ff, 27
 - elastic_change_fpca, 28
 - elastic_ph_change_ff, 30
 - f_to_srvf, 35
 - gam_to_v, 36
 - gradient, 37
 - horizFPCA, 38
 - inv_exp_map, 40
 - invertGamma, 40
 - jointFPCA, 41
 - multivariate_karcher_mean, 47
 - optimum.reparam, 48
 - outlier.detection, 50
 - predict.hfPCA, 58
 - predict.jfPCA, 59
 - predict.lpcr, 59
 - predict.mlpcr, 60
 - predict.pcr, 61
 - predict.vfPCA, 62
 - q_to_curve, 62
 - reparam_curve, 63
 - resamplecurve, 65
 - sample_shapes, 66
 - smooth.data, 69
 - SqrtMean, 70
 - SqrtMeanInverse, 71
 - SqrtMedian, 71
 - srvf_to_f, 72
 - v_to_gam, 77
 - vertFPCA, 76
 - warp_f_gamma, 78
 - warp_q_gamma, 79
- * **tolerance**

bootTB, 6
*** warping**
 rgam, 66

 align_fPCA, 3

 beta, 5
 bootTB, 6
 boxplot.ampbox (boxplot.fda.warp), 7
 boxplot.fda.warp, 7
 boxplot.fda.warp(), 7, 8
 boxplot.phbox (boxplot.fda.warp), 7

 calc_shape_dist, 8
 curve_depth, 9
 curve_geodesic, 10
 curve_karcher_cov, 11
 curve_karcher_mean, 11
 curve_pair_align, 13
 curve_principal_directions, 14
 curve_srvf_align, 15
 curve_to_q, 16

 elastic.depth, 17
 elastic.distance, 18
 elastic.logistic, 19
 elastic.lpcr.regression, 20
 elastic.mlogistic, 21
 elastic.mlpcr.regression, 22
 elastic.pcr.regression, 24
 elastic.prediction, 25
 elastic.regression, 26
 elastic_amp_change_ff, 27
 elastic_change_fPCA, 28
 elastic_ph_change_ff, 30

 f_to_srvf, 35
 fdasrvf, 31
 fdasrvf-package (fdasrvf), 31
 foreach(), 19, 22, 26, 46
 foreach::foreach(), 44
 function_group_warp_bayes, 32
 function_mean_bayes, 34

 gam_to_v, 36
 gauss_model, 36
 gradient, 37
 growth_vel, 38

 horizFPCA, 38

 im, 39
 inv_exp_map, 40
 invertGamma, 40

 joint_gauss_model, 42
 jointFPCA, 41

 kmeans_align, 43

 LongRunCovMatrix, 45

 multiple_align_functions, 46
 multivariate_karcher_mean, 47

 optimum.reparam, 48
 outlier.detection, 50

 pair_align_functions, 51
 pair_align_functions_bayes, 52
 pair_align_functions_expmmap, 54
 pair_align_image, 56
 pcaTB, 57
 predict.hfPCA, 58
 predict.jfpca, 59
 predict.lpcr, 59
 predict.mlpcr, 60
 predict.pcr, 61
 predict.vfPCA, 62

 q_to_curve, 62

 reparam_curve, 63
 reparam_image, 64
 resamplecurve, 65
 rgam, 66

 sample_shapes, 66
 simu_data, 67
 simu_warp, 68
 simu_warp_median, 68
 smooth.data, 69
 SqrtMean, 70
 SqrtMeanInverse, 71
 SqrtMedian, 71
 srvf_to_f, 72

 time_warping, 36, 38, 41, 42, 73, 76
 time_warping(), 7, 50, 68, 69, 76
 toy_data, 75
 toy_warp, 76

v_to_gam, [77](#)

vertFPCA, [76](#)

warp_f_gamma, [78](#)

warp_q_gamma, [79](#)